

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Wyandotte NW NE NW E			8	T 11 S	R 25 East
Distance and direction from nearest town or city street address of well if located within city? 1015 N. 29th St. (N edge)					
2 WATER WELL OWNER:					
RR#, St. Address, Box # :	Amoco 11660 W. 85th				
City, State, ZIP Code :	Wenatchee KS 66214				
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL. 25 ft. ELEVATION:				
 Mile scale bar: 0 to 1 mile. Directional labels: N, S, E, W.	Depth(s) Groundwater Encountered 1. .ft. 2. .ft. 3. .ft.				
	Well's Static Water Level 20 ft. below land surface measured on mo/day/yr				
	Pump test data: Well water was .ft. after hours pumping gpm				
	Est. Yield gpm: Well water was .ft. after hours pumping gpm				
	Bore Hole Diameter 6 in. to 25 ft., and in. to .in. to .ft.				
WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued Clamped <input checked="" type="checkbox"/> PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded					
Blank casing diameter 2 in. to 25 ft., Dia lbs./ft. Wall thickness or gauge No.					
Casing height above land surface .in., weight					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 25 ft. to 15 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 15 ft. to 13 ft., From ft. to ft.					
6 GROUT MATERIAL:					
Grout Intervals: From 13 ft. to 11 ft., From Bentonite 4 Other ft. to ft.					
What is the nearest source of possible contamination?					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? How many feet?					
FROM TO		LITHOLOGIC LOG	FROM TO	PLUGGING INTERVALS	
0	25	Bra Silty Clay			
		Mw 6			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 12-11-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 6688 This Water Well Record was completed on (mo/day/yr) 12-11-95 under the business name of Max Enterprises by signature David Hartzler					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY AND PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					