	WATER WE	ELL RECORD Fo	orm WWC-5	KSA 82a	a-1212			N	IW A	12	
1 LOCATION, OF WATER WELL:	Fraction		Sect	tion Number	Town	nship Nun			ange Num		
County: WYAN COTTE	1 NW 1/4 S			31	Ţ	//_	s	R	25	® W	
Distance and direction from nearest town of SHAVINEF D		s of well if located v	within city?								
2 WATER WELL OWNER: MTCD O	DI COMDAN	NY , C/O M	.K. Hu	dson							
RR# St Address Box # サム はん)	X マスト	•				•	riculture, D	ivision (of Water I	Resources	
City, State, ZIP Code : KNNSA	S CIRY K	ANSAS 1	حراالكاف	<u> </u>		plication I					
3 LOCATE WELL'S LOCATION WITH 4	DEPTH OF COMPL	LETED WELL	1. 8	. ft. ELEVA							
NDe	epth(s) Groundwater /ELL'S STATIC WAT										
		t data: Well water v									
NW NE Es	st. Yield									_	
• [ore Hole Diameter.	7.1.4 in. to	18'		and		in.	to			
	VELL WATER TO BE		Public water			ditioning	11 l	njection	well		
SW SE	1 Domestic				_		12 (
	2 Irrigation			arden only	_						
	/as a chemical/bacter nitted	riological sample suc	omitted to De					mo/day/	-	∍ was sub-	
5 TYPE OF BLANK CASING USED:	· · · · · · · · · · · · · · · · · · ·	Vrought iron	8 Concre		ater Well Dis		? Yes ITS: Glued		No		
1 Steel 3 RMP (SR)		Asbestos-Cement		ne the (specify belov		NG JOH			. Clamped		
PVC 4 ABS		iberglass	•		•				· · · · · · · · · · · · · · · · · · ·		
Blank casing diameter in.	. to &	. ft., Dia	in. to		ft., Dia	ı . <i></i>	i	n. to	. <i></i> .	ft.	
Casing height above land surface	in., ν	weight . Sch E D) 40	Ibs./	/ft. Wall thic	kness or	gauge No				
TYPE OF SCREEN OR PERFORATION N	<u> </u>		Ø PV			10 Asbes	stos-cemer	nt			
1 Steel 3 Stainless st		iberglass		P (SR)			r (specify) .				
2 Brass 4 Galvanized SCREEN OR PERFORATION OPENINGS		Concrete tile	9 ABS		12 None used (o 8 Saw cut			open hole) 11 None (open hole)			
1 Continuous slot 3 Mill s			5 Gauzed wrapped 6 Wire wrapped		9 Drilled			11 Nor	ie (open i	hole)	
2 Louvered shutter 4 Key		7 Torch cu	• •								
SCREEN-PERFORATED INTERVALS:	From 1. 2 .	ft. to		ft., Fro	m		ft. to	· · · · · · · ·			
	From	ft. to		ft., Fror	om		ft. to) <i></i> .		ft.	
GRAVEL PACK INTERVALS:	From /. 8	ft. to	7							ft.	
	From	ft. to	4	ft., From							
6 GROUT MATERIAL: 1 Neat cerr Grout Intervals: Fromft.	ment			nite 4							
What is the nearest source of possible cor		II., FIUIII	14. 4		II., F stock pens						
1 Septic tank 4 Lateral li		7 Pit privy		11 Fuel storage			14 Abandoned water well 15 Oil well/Gas well				
2 Sewer lines 5 Cess po	ool	8 Sewage lagoon		12 Fertilizer storage					ecify below	w)	
Watertight sewer lines 6 Seepage	e pit	9 Feedyard		13 Insec	cticide stora	•					
Direction from well? WEST	: :=: :0: 00:0 00			How mai	iny feet?	<u>40</u>					
FROM TO	LITHOLOGIC LOG		FROM	то		PLU	IGGING IN	TEHVA	LS		
4" 3 Fill 119	Fire /					-					
31 10' BIN Pla	stic Cla										
101 17 Ber to	TAH Sil	Av Clay									
17 18 Fractul	ad limit	= StodE									
											
											
CONTRACTOR'S OR LANDOWNER'S completed on (mo/day/year)	CERTIFICATION:	This water well was	construc	ted, (2) reco	onstructed, o	or (3) plu	igged unde	ər my ju	ırisdiction	and was	
							of my kno	wiedge	and belief	f. Kansas	
Water Well Contractor's License No.		This Water Well	<i>.</i>			グクト		/:	. 1 7.1	5	
under the business name of XU/ +2 INSTRUCTIONS: Use typewriter or ball point pen.	ENU/OF			by (signat		ML,	rs.	-1 to K			
INSTRUCTIONS: Use typewriter or ball point pen. of Health and Environment, Bureau of Water, Top								opies to K	ansas Depa	rtment	