

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Wyandotte		Fraction SW 1/4 SW 1/4 NW 1/4	Section Number 20	Township Number T 11 S	Range Number R 25 EW																																										
Distance and direction from nearest town or city, street address of well if located within city? 3401 Fairbanks Ave. Kansas City, KS.																																															
2 WATER WELL OWNER: Sinclair Oil Co. RR#, St. Address, Box # : 3401 Fairbanks Ave. City, State, ZIP Code : Kansas City, KS. Board of Agriculture, Division of Water Resources Application Number:																																															
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 35' ft. ELEVATION:																																													
		Depth(s) Groundwater Encountered 1. 26' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 26.37 ft. below land surface measured on mo/day/yr 4-29-97 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 10 1/2 in. to 35' ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No																																													
		5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Blank casing diameter 2.375 in. to 20' ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 2' in., weight lbs./ft. Wall thickness or gauge No. SDR 13 SCH 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)																																													
		SCREEN-PERFORATED INTERVALS: From 35' ft. to 20' ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 35' ft. to 18' ft., From ft. to ft. From ft. to ft., From ft. to ft.																																													
		6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 18' ft. to 15' ft., From 15' ft. to 0 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? North How many feet? 250'																																													
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>2</td> <td>Grass-dk brn rubble fill, brick, glass, concrete, clay, moist.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>7</td> <td>Med-lt brn clayey silt to silt, dry, faint odor, soft.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>7</td> <td>10</td> <td>Dk gray-blue gray silty clay to clayey silt, moist, firm, faint-mod. odor.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>10</td> <td>15</td> <td>gray fine sand, mod-strong odor, moist, well rounded &amp; sorted.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>15</td> <td>25</td> <td>Fine-med gray sand, mod-strong odor, moist, well sorted.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>25</td> <td>35</td> <td>Blk-dk gray wet sand, fine-very coarse w/ few pebbles, very strong odor.</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	2	Grass-dk brn rubble fill, brick, glass, concrete, clay, moist.				2	7	Med-lt brn clayey silt to silt, dry, faint odor, soft.				7	10	Dk gray-blue gray silty clay to clayey silt, moist, firm, faint-mod. odor.				10	15	gray fine sand, mod-strong odor, moist, well rounded & sorted.				15	25	Fine-med gray sand, mod-strong odor, moist, well sorted.				25	35	Blk-dk gray wet sand, fine-very coarse w/ few pebbles, very strong odor.			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																										
0	2	Grass-dk brn rubble fill, brick, glass, concrete, clay, moist.																																													
2	7	Med-lt brn clayey silt to silt, dry, faint odor, soft.																																													
7	10	Dk gray-blue gray silty clay to clayey silt, moist, firm, faint-mod. odor.																																													
10	15	gray fine sand, mod-strong odor, moist, well rounded & sorted.																																													
15	25	Fine-med gray sand, mod-strong odor, moist, well sorted.																																													
25	35	Blk-dk gray wet sand, fine-very coarse w/ few pebbles, very strong odor.																																													
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-23-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-7-97 under the business name of JB Environmental Drilling by (signature) James Becker																																															