· ··				R WELL RECORD	Form WWC-					l
	ON OF WA	TER WELL:	Fraction 1/4	NW 14 N	1	7 Number	Township Numb	er S	Range N	
Distance a	direction			ddress of well if locat		-				
<u> 40</u>	lown		10	1	5.4					
2 WATER	R WELL OW	NER: Han	lana Hay	e Funual 7	aie					
	Address, Bo	×# : 4156-	remach				Board of Agric	ulture, Divis	sion of Wat	er Resources
City State	7ID Code	KAN	CAMPITU L	15			Application Nu	mber:		
LOCATE	WELL'S L	OCATION WITH	4 DEPTH OF C	OMPLETED WELL.	354	ft. ELEVA	TION:			
→ AN "X"	IN SECTIO	N BOX:	Denth(s) Ground	lwater Encountered	129'	ft. 2		ft. 3	<u></u> .	
- F	1		WELL'S STATIC	WATER LEVEL	25' ft	below land sur	face measured on mo	/dav/vr 3-	21-97	7 <i></i>
1	i		ľ				iter ho			
-	- NW	NE					iter ho			
	İ	!!!	Dara Hala Diam	Significant	at'	IL. a.	and	in to	''g	#
* w -		E					8 Air conditioning		ction well	
_	-			TO BE USED AS:	5 Public wat		=	•	er (Specify	holow)
-	- SW	SE	1 Domestic	3 Feedlot			9 Dewatering			
	1	1 1	2 Irrigation	4 Industrial			Monitoring well			
<u> </u>				bacteriological sample	submitted to L		esNo.X		<i>-</i>	npie was sub
.		<u> </u>	mitted				ter Well Disinfected?	•	(No)	
		CASING USED:		5 Wrought iron	8 Conc		CASING JOINTS			•
1 Ste		3 RMP (S	R)	6 Asbestos-Cement	t 9 Other	(specify below	v)			
2 PV	C	4 ABS	0-1	7 Fiberglass					d. 🔥	
Blank casi	ng diameter	a.5.15	in. to .25.'				ft., Dia			ft.
Casing hei	ight above la	and surface Z		.in., weight	<u></u>		ft. Wall thickness or g	auge No. 🕻	שַאַיַתיצ	
TYPE OF	SCREEN O	R PERFORATIO	N MATERIAL:		7 P	/C)	10 Asbesto	s-cement	SDR	3
1 Ste	el	3 Stainles	s steel	5 Fiberglass	8 RI	MP (SR)	11 Other (s	specify)	<i></i>	
2 Bra	ass	4 Galvania	zed steel	6 Concrete tile	9 AI	3S	12 None us	sed (open	hole)	
SCREEN (OR PERFO	RATION OPENIN	IGS ARE:	5 Gau	zed wrapped		8 Saw cut	11	None (op	en hole)
1 Co	ntinuous slo	ot (3 N	fill slot	6 Wire	wrapped		9 Drilled holes			
2 Lo	uvered shut	ter 4 K	ey punched		ch cut.	•	10 Other (specify)			
SCREEN-I	PERFORAT	ED INTERVALS:	• .	1. 34 ft. to	24	ft. Fron	n	ft. to		
			From	ft. to	_	ft From	n	ft to		ft.
ď	GRAVEL PA	CK INTERVALS:	From	.35.1 ft. to	21	ft Fror	n	. ft. to		
			From	ft. to		# Eror		ft. to		ft.
6 GROUT	MATERIAL	. 1 Neat		2 Cement grout	4'3Bent	onite / 4	Other			
Grout Inter			<i>\(\alpha'\)</i>	ft., From	4	to D	ft., From			
		ource of possible	contamination		(2)		ock pens		doned wate	
	ptic tank	·	ral lines	7 Pit privy	•		storage Heating		ell/Gas wel	
	wer lines	_				TO Footili	zer storage			
		5 Cess	•	8 Sewage la	lgoon			16 Other	(specify b	elow)
		ver lines 6 Seep	page pit	9 Feedyard			ticide storage			
FROM	rom well? (JOLLIU	LITHOLOGIC	100	FROM		ny feet? 6	GING INTE	DVALC	
	1.25	Mara NA	LITHOLOGIC	LOG	FROM	ТО	FLOG	SING INTE	INVALO	
0	1.65	SULSS - DRO	noittyclay	1.1005tm2.00f	c +	+				
10-		earthy of	_	• • • • • • • • •	, .	 				
1.25	5 .50		4,400s, fi	um,nocaou,il	DC4)—	+				
	100	red plass			<u> </u>	 				
వ్.50	19.0	Lt-Healis	routyeery	WOKALOWIDE	Stained	ļ. <i></i>				
		HOTTLENG,	tum, no oda	HOUSE LOW-	Helplast	KIZY				
19.0	22.75	HEAL BUT U	lay typhs,	no odou, dam	30	1				
		Med place	stilly		`_ .	ļ				
22.75	35.0	MALLABU	clayey six		aso					
		towetat	29, no oda	L, BKBLAOIL	tu					
		Hottles				<u> </u>				
										
	1									
						1				
]	L	I		IOAL Th' "					my juricelie	ion and was
				ION: This water well	was (1) donstr		nstructed, or (3) plugg			
		/year) . 3-20					rd is true to the best of		gge and b	ellei. Nansas
Water Wel	I Contractor	's License No.) 37 ,	This Water	Well Record w		on (mo/day/yr) . 3.	82.4	£	
	business na		NULLSTIMEN	tal Drulle	na	by (signat		WLL	w	
INSTRU	CTIONS: Use ty	pewriter or ball point	pen. PLEASE PRESS I	FIRMLY and PRINT clearly.	Please fill in blanks	underline or circle	the correct answers. Send t	op three copie	es to Kansas (Department
of Healt	th and Environn	nent, Bureau of Water	, Topeka, Kansas 6662	20-0001. Telephone: 913-296	6-5545. Send one to	WATER WELL OV	NNER and retain one for you	ir records.		