

1 LOCATION OF WATER WELL: County: Wyandotte		Fraction: NE 1/4 NE 1/4 SE 1/4	Section Number: 3	Township Number: T 11 S	Range Number: R 25 E
Distance and direction from nearest town or city street address of well if located within city? 1315 Fairfax, Kansas City, KS.					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		City of Kansas City/Don Jones 701 N. 7th Kansas City, KS. 66101			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 20' ft. ELEVATION: Depth(s) Groundwater Encountered 1. - ft. 2. - ft. 3. - ft. WELL'S STATIC WATER LEVEL Dry ft. below land surface measured on mo/day/yr 3-24-97 Pump test data: Well water was - ft. after - hours pumping - gpm Est. Yield - gpm; Well water was - ft. after - hours pumping - gpm Bore Hole Diameter 8 1/2" in. to 20' ft., and - in. to - ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes - No X; If yes, mo/day/yr sample was submitted - Water Well Disinfected? Yes - No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 2.375 in. to 9 1/6" ft., Dia - in. to - ft., Dia - in. to SDR 13 ft. Casing height above land surface Flush mt. in., weight - lbs./ft. Wall thickness or gauge No. SCH 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 10 Asbestos-cement 11 Other (specify) - 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) - SCREEN-PERFORATED INTERVALS: From 19'6" ft. to 9'6" ft., From - ft. to - ft. GRAVEL PACK INTERVALS: From 19'6" ft. to 7' ft., From - ft. to - ft. 6 GROUT MATERIAL: 1 Neat cement 3 Cement grout 5 Bentonite 4 Other - Grout Intervals: From 7'3" to 5' ft., From 5' to 0' ft., From - ft. to - ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? East North East How many feet? 190'					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	.50	Asphalt			
.50	2	Ls Rx. gravel, dry, hard, packed.			
2	11.50	Med brn fine-coarse sand, dry, no odor, well graded.			
11.50	18	Gray-dk gray mottled clay, highly plastic, moist.			
18	20	Gray clayey silt to silt, dry to moist, no odor, firm.			
			Flush mt. OK'd by Don Taylor		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-12-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/year) 3-25-97 under the business name of JB Environmental Drilling by (signature) James Bueber					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY
T
R
EW
SEC.