		WATER	WELL RECORD F	orm WWC-5	KSA 828			
1 LOCATION OF V	1 4	Fraction			tion Number	1		Range Number
County: Wyan	ion from nearest town o	NE 14	SE 1/4 NW		22	<u> </u>	s	R 25 EW
Distance and direct	ion from nearest town o	or city street add	ress of well if located	within city?				MW-5
A 14/4-TED 14/ELL	OWNER: Graham	1 - ok o						<u>///W-2</u>
	DWNEH: Graham Box # : 721 S. P.					Board of Ac	rioulturo F	Division of Water Resource
	de : <u>Lansas</u>		66015			Application		DIVISION OF WATER RESOURCE
Oily, State, ZIP COR	ELOCATION WITH	DEDTIL DE DO	95-07-5	230	4 FLEVA	74	Z 34	G.L
AN "X" IN SECT	ION BOX:	DEPTH OF COM	MPLETED WELL	17.0	.π.ELEVA	ATION:	4: <i>U.</i> F	
- [N Det	ptn(s) Groundwa	MATERIEVEL 1.	34 4 4	r II	food modeured on i	no/dov/vr	6/4/97
† i								mping gpm
NW -	NE Est							mping gpm
! ! `	 		- · - · · ·					toft.
* w		ELL WATER TO		Public wate		8 Air conditioning		Injection well
- i		1 Domestic				9 Dewatering		Other (Specify below)
SW -	SE	2 Irrigation					12 \	
1 !	l wa	_				V		mo/day/yr sample was sub
<u> </u>	S mitt		steriological sample st	ionnitied to De	=	ater Well Disinfected	=	No X
5 TYPE OF BLAN	K CASING USED:		Wrought iron	8 Concre				I Clamped
1. Steel	3 RMP (SR)		Asbestos-Cement		specify belo			ed
②PVC	4 ABS	_	' Fiberglass			w <i>)</i> 		ded
								in. to , ft.
	e land surface							sch 40
	OR PERFORATION M		., weight	7 p v	· · · · · · · · · · · · · · · · · · ·		stos-ceme	
1 Steel	3 Stainless ste		Fiberglass	8 RM				····
2 Brass	4 Galvanized s		Concrete tile	9 AB:			used (op	
	FORATION OPENINGS			d wrapped	3	8 Saw cut	useu (op	11 None (open hole)
1 Continuous			6 Wire w			9 Drilled holes		11 None (open noic)
2 Louvered sl	•		7 Torch	• •				
	ATED INTERVALS:	From /	3 # to	23	4 Ero	m	# +/	o
CONTENT EN ON								o
GRAVE								o
GHAVEE		From	ft. to			m		
6 GROUT MATER			Cement grout	③Bento				
Grout Intervals:	From 🗘 ft i	to 10 -	ft From 16) fi	12			ft. to ft.
	t source of possible conf			.		stock pens		pandoned water well
1 Septic tank	•		7 Pit privy		11 Fuel	•		il well/Gas well
2 Sewer lines			8 Sewage lago	าก		lizer storage		
3 Watertight s	sewer lines 6 Seepage		9 Feedyard	211		cticide storage	Ü	ther (specify below)
Direction from well	, •	, р.	o i ccayara			iny feet?		
FROM TO		LITHOLOGIC LO	OG .	FROM	TO		GGING IN	NTERVALS
0 14	Asphalt							
	7,750							
.4 5	Fine Sand	Brown	c. the must					
	1110000	1 /2/00/1	1.17,100131					
5 10	Sitt come	- honers . S	one fire sand					
J / / /			ONE THE SPACE	<u> </u>				
	120.21					 		
10 23	Can to Mad	1100 Sand	Prown Silty					
	moist	2000	11001(300)					
				t				
·								
				<u> </u>				
				+				
				-				
								er my jurisdiction and was
completed on (mo/d		30/27					t of my kno	owledge and belief. Kansas
Water Well Contract			This Water We	II Record wa	-	4 (77)	6/6/9	и
under the business		n/KCIL			by (signa		Vay_	
INSTRUCTIONS: Us	se typewriter or ball point pen.	PLEASE PRESS FIRM	ALY and PRINT clearly. Plea	se fill in blanks, t	Inderline or circle	e the correct answers. Se	nd top three o	copies to Kansas Department
or Health and Envir	coment bureau of Water Took	esa, sansas bobzu-0	reieunone: 913-290-55	70. OEHU UHE 10	TO THE U	THE THE PERSON OF THE PERSON O	,	