Distance and direction from nearest town or city street address of well if located within city? 2313 W. 43rd Street, Kansas City, Ks. Beverly Gates 10115 Womanga Lane	lumber
Distance and direction from nearest town or city street address of well if located within city? 2313 W. 43rd Street, Kansas City, Ks. Beverly Gates 10155 Wordpage Lane	_
2313 W. 43rd Street, Kansas City, Ks. Beverly Gates 10115 Worongs Lane	E)W
10115 Worongs Tane	
10175 Wordner Jane	·
INF. 31. Addition Double of Agriculture, Division of trate	er Resource
City State ZIP Code Leawood, Ks. 66206 Application Number	
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 17' ft. ELEVATION:	
	,
WELL'S STATIC WATER LEVEL 6.20 ft. below land surface measured on mo/day/yr 9-14-98.	
Pump test data: Well water was ft. after hours pumping	
Est. Yield gpm; Well water was ft. after hours pumping	opm
Boys Hote Diameter X'/D in to 17	
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well	
1 Domestic 3 Feedlot 6 Oil field water supply 9—Dewatering 12 Other (Specify t	below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes; If yes, mo/day/yr sample submitted to Department?	nple was sut
S mitted Water Well Disinfected? Yes No	•
TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamp	ped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
2 PVC 4 ABS 7 Fiberglass Threaded X	
Blank casing diameter 2.3.75in. to .7	13 ft.
Casing height above land surface # COSON TELL in., weight	. 4.0
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open	en hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From	
From ft. to	
GRAVEL PACK INTERVALS: From. 1.7	
From ft. to ft., From ft. to GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From	
1 Septic tank 4 Lateral lines 7 Pit privy (11) Fuel storage Fourier 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify bel	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? East	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0 50 Asphalt	
.50 12 Dk cray-green mottled silty	
clay, slight odor, firm to	
clay, slight odor, firm to soft, med. plasticity.	
clay, slight odor, firm to	
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor.	
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley	
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor.	
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley	
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley clay, dry, stiff, no odor.	
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley clay, dry, stiff, no odor.	ylor
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley clay, dry, stiff, no odor.	vlor
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley clay, dry, stiff, no odor.	vlor
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley clay, dry, stiff, no odor.	vler_
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley clay, dry, stiff, no odor. Fl. mt. OK'd by Don Tay	
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley clay, dry, stiff, no odor. Fl. mt. OK'd by Don Tay	
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley clay, dry, stiff, no odor. Fl. mt. OK'd by Don Tay CONTRACTOR'S OB LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdictic completed on (mo/day/was) 1.0.539 and this record is true to the best of my knowledge and believed.	
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley clay, dry, stiff, no odor.	
clay, slight odor, firm to soft, med. plasticity. 12 15 Red brn stiff tight clay w/ oxides, damp, no odor. 15 17 Yellow gray weathered shaley clay, dry, stiff, no odor. Fl. mt. OK'd by Don Tay CONTRACTOR'S OB LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction ompleted on (mo/day/lear). 539 and this record is true to the best of my knowledge and believed.	ion and was