

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1] LOCATION OF WATER WELL: County: Wyandotte		Fraction SE ¼ SW ¼ NW ¼	Section Number 19	Township Number T 11 S	Range Number R Z5 EW
Distance and direction from nearest town or city street address of well if located within city? 4515 Kansas Ave Kansas City, KS					
2] WATER WELL OWNER: The Burlington Northern and Santa Fe Railway Co. RR#, St. Address, Box # : 4200 Deen Road Board of Agriculture, Division of Water Resources City, State, ZIP Code : Fort Worth, TX 76106 Application Number:					
3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4] DEPTH OF COMPLETED WELL 30 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 9 / 1 / 98 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter . 6 ½ in. to . 30 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ⑩ Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
A diagram showing a section box divided into four quadrants labeled NW, NE, SW, and SE. A vertical arrow on the left indicates North (N), and horizontal arrows at the top indicate West (W) and East (E).					
5] TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) ② PVC 4 ABS Blank casing diameter 2 in. Dia 15 in. Dia ft. Dia in. Dia ft. Casing height above land surface 0 in. weight 0-7 lbs./ft. Wall thickness or gauge No. Sch 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ③ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 30 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 13 ft. to 30 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6] GROUT MATERIAL: ① Neat cement 2 Cement grout ③ Bentonite 4 Other Grout intervals: From 1 ft. to 10 ft. From 10 ft. to 13 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
4	6	Brown clayey silt, dry			
6	10	Brown sandy silt, moist			
10	14	Brown to black silty clay, dry			
14	16	Light brown sandy silt, dry			
16	30	Brown to black silt, moist			
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9 / 1 / 98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 . This Water Well Record was completed on (mo/day/yr) 10 / 16 / 98 under the business name of Layne Christensen Company by (signature) Nate Baldwin					