


LOCATION OF WATER WELL: Wyandotte
 Fraction: SW NW SE SW SW Section Number: 20 Township Number: T 11 S Range Number: R 25 EW

Address and direction from nearest town or city street address of well if located within city?
 7 Strong Avenue, Kansas City, KS

WELL OWNER: City of Kansas City, Kansas
 St. Address, Box #: One McDowell Plaza
 Date, ZIP Code: Kansas City, KS 66101
 Board of Agriculture, Division of Water Resources
 Application Number:

DATE WELL'S LOCATION WITH "X" IN SECTION BOX: [Diagram] DEPTH OF COMPLETED WELL: 43 ft ELEVATION: 709.37 ms1



Depth(s) Groundwater Encountered: 1. 27 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 26.97 ft. below land surface measured on mo/day/yr 6/18/91
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 9 in. to ft. and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:
 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded

Casing diameter: 2 in. to ft., Dia. in. to ft., Dia. in. to ft.
 height above land surface: -0.25 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40

TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)

TYPE OF PERFORATION OPENINGS ARE:
 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

NON-PERFORATED INTERVALS: From 22.5 ft. to 42.5 ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 22.5 ft. to 43 ft., From ft. to ft., From ft. to ft.

PLUGGING MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Cement/Bentonite grout
 Intervals: From 0 ft. to 22.5 ft., From ft. to ft., From ft. to ft.

Is the nearest source of possible contamination:
 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well
 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well
 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)
 How many feet? West

TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
8.5	Silty Clay			
11	Fine Sand			
17.5	Clayey Sylt			
43	Fine to Medium Sand			

TRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was drilled on (mo/day/year) 6/5/91 and this record is true to the best of my knowledge and belief. Kansas Well Contractor's License No. 529 This Water Well Record was completed on (mo/day/yr) 8/9/91 by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

077