		WATER	WELL RECORD	Form WWC-				
LOCATION OF WA	, ,	Fraction	14.7	_ 1	ction Number	Township Num	l l	Range Number
County: Wyah	dote	1/4	NW 4SI		19	<u> </u>	S	R25 (E)N
Distance and direction						. 1 1		LC
1,190	ENE	04 4	JULY.	rgenti	ne b	lud, Ary	HATI	re, as
WATER WELL ON	INER: GATX	termi	nal Corp					
RR#, St. Address, Bo	x#:500 (west h	10HLOE'S	4 ,		_	•	sion of Water Resource
City, State, ZIP Code	CMCG	ryo, I	L 6060	61-36	27)	Application N		
LOCATE WELL'S L	OCATION WITH 4	DEPTH OF CO	OMPLETED WELL	29.5	ft. ELEVA	TION:7.5.8.4.	2	
AN "X" IN SECTIO	<u>v </u>							ft.
ī !	┌ ! w			•				<i>8:-1.</i> 799
NW	NE							ing gpm
l [- ''j'	E							ing gpm
# w - !		ore Hole Diame	ter.72.5in. t	o2.G S	Ž	and	in. to	
ž " [!	W W	ELL WATER TO	O BE USED AS:	5 Public wa	er supply	8 Air conditioning	11 Inje	ection well
-	X !	1 Domestic	3 Feedlot	6 Oil field w	ater supply	9 Dewatering	12 Oth	ner (Specify below)
'''	;;	2 Irrigation	4 Industrial	7 Lawn and	garden only	10 Monitoring well .		
. L i	<u> </u>	/as a chemical/b	acteriological sample	submitted to I	Department? Y	esNo	; If yes, me	o/day/yr sample was sut
	ş m	itted			Wa	ter Well Disinfected?	Yes	No
TYPE OF BLANK	CASING USED:		5 Wrought iron	8 Cond	rete tile	CASING JOINT	ΓS: Glued .	Clamped
1 Steel	3 RMP (SR)		6 Asbestos-Cemen	t 9 Othe	(specify below	v)	Welded	
2 PVC	4 ABS		フ Fiberglass				Threade	
Blank casing diameter	· 	. to 9.45	ft., Dia	in. t	.	ft., Dia	in.	to ft.
Casing height above I	and surface	<i>D</i>	in., weight	<u></u>	lbs./	ft. Wall thickness or	gauge No.	sch 40
TYPE OF SCREEN C				(7 P			tos-cement	
1 Steel	3 Stainless s	teei	5 Fiberglass	8 R	MP (SR)	11 Other	(specify)	
2 Brass	4 Galvanized	steel	6 Concrete tile	9 A	38	12 None	used (open	hole)
SCREEN OR PERFO	RATION OPENINGS	S ARE:	5 Gau	zed wrapped		8 Saw cut	1	1 None (open hole)
1 Continuous sk	ot 3 Mill	slot	6 Wire	wrapped		9 Drilled holes		, ,
2 Louvered shut	ter 4 Key	punched	7 Toro	ch cut		10 Other (specify)		
SCREEN-PERFORAT			.5 ft. to	29,5	ft Fro			
			ft. to					
GRAVEL PA	CK INTERVALS:	From	' ft. to	J. 9. 5				
		From	ft. to		ft., Fro			ft.
GROUT MATERIA	_	•	2 Cement grout	3 Bent				
Grout Intervals: Fro	m / ft.	to	ft., From	ft.	to	ft., From		ft. to
What is the nearest s	ource of possible co	ntamination:			10 Lives	tock pens		ndoned water well
 Septic tank 	4 Lateral		7 Pit privy		11 Fuel	•		/ell/Gas well
2 Sewer lines	5 Cess po		8 Sewage la	goon		zer storage	6 Othe	specify below)
3 Watertight sev	ver lines 6 Seepag	e pit	9 Feedyard			ticide storage .	. Acun.	x. Skop
Direction from well?					How ma		20110 1117	-5.41.6
FROM TO		LITHOLOGIC L	<u>.OG</u>	FROM	ТО	PLUC	GGING INTI	=HVALS
0 1.5	F://				1			
1.5 5.0	Clay-me	oduled	brown 4 gra		1			
	trace org	anics	med. plast	ickoy ,	1			
	damp.	 			+			
5.0 23.5	S/17 - X	ight 6	rown, fin	,	-			
	to loose	, dry h	salura	red	 			
	@ 33/				1			
23.5 29.5	Sand -	Lt. brou	on, fine		<u> </u>			
	graneo	I, saku	rated		1			
	ļ. "				 			
	ļ							
					↓ ∔			
					<u> </u>			
CONTRACTOR'S	OR I ANDOWNED'S	CERTIFICATION	ON: This water well	was (1) constr	ucted (2) reco	enstructed, or (3) plus	aged under	my jurisdiction and wa
completed on (mo/day		77 9.9		(1) 301311				edge and belief. Kansa
Water Well Contractor		616	This Water	Well Record w		on (mo/day/yr)		99
water well Contractor under the business na	_ 4 .	- / -	tech In		by (signa		120-	Sursin
							tion three are	ine to Kanesa Danatara
INSTRUCTIONS: Use t	pewriter or ball point pen	. PLEASE PRESS FI	RMLY and PRINT clearly. I	Please fill in blanks	underline or circle	the correct answers. Send NNER and retain one for y	top three copi	es to Kansas Department