

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Wyandotte</u>		<u>NW 1/4 SE 1/4 SE 1/4</u>	<u>3</u>	<u>T 40N S</u>	<u>R 25 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1421 N. 3rd St. KC. KS. 64101</u>					
2 WATER WELL OWNER: <u>KANSAS GAS SERV.</u>					
RR#, St. Address, Box #: <u>501 S.W. GAGE Blvd.</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: <u>Topeka, KS</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>45.5</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>21</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: <u>8 1/4</u> in. to <u>45-5</u> ft., and in. to ft.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>M.W.-85</u>					
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2</u> in. to <u>37</u> ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>Flush</u> in., weight lbs./ft. Wall thickness or gauge No. <u>Sched 40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From <u>45.5</u> ft. to <u>37</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>45.5</u> ft. to <u>36</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>45.5</u> ft. to <u>2</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	25	Dark Grey Silty Clay			
25	30	Grey Silty Clay			
30	45.5	Light grey to Dark grey Silty Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5/27/99</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>650</u> This Water Well Record was completed on (mo/day/yr) <u>12/26/99</u> under the business name of <u>DFS</u> by (signature) <u>[Signature]</u>					