

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Wyandottaw</u>		<u>N 1/4 SE 1/4 SE 1/4</u>	<u>3</u>	T <u>40N</u> S	R <u>25</u> E/W
Distance and direction from nearest town or city street address of well if located within city? <u>1421 N. 3rd St. KC. KS 66101</u>					
2 WATER WELL OWNER: <u>KANSAS GAS SERV.</u>					
RR#, St. Address, Box #: <u>501 SW CAGE Blvd.</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: <u>TOPEKA, KS</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>42.1</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>32.7</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>MAN-11D</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>Push</u> in., weight lbs./ft. Wall thickness or gauge No. <u>Sched 40</u> TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 6 Wire wrapped 9 Drilled holes 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>42.1</u> ft. to <u>32.0</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>42.1</u> ft. to <u>31.1</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From <u>31.1</u> ft. to <u>2</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Gravel fill			
2	13	gray silt/clay			
13	16	gray clay silt			
16	22	gray silt/sand			
22	25	gray green silt/sand			
25	42.1	gray silt/clay (gray)			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11/23/99</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>650</u> This Water Well Record was completed on (mo/day/yr) <u>6/29/00</u> under the business name of <u>DFS</u> by (signature) <u>[Signature]</u>					