

WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No.

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Wyandotte		NW 1/4 SW 1/4 NW 1/4	2	T 11 S	R 25 EW
Distance and direction from nearest town or city street address of well if located within city? 1601 Fairfax Trfy. Kansas City, KS					
2 WATER WELL OWNER: Lady Baltimore Foods, Inc.					
RR#, St. Address, Box #: 1601 Fairfax Trfy.				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: Kansas City, Ks. 66115				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 35' ft. ELEVATION: 28' ft.			
		Depth(s) Groundwater Encountered 1. 28' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 25.29' ft. below land surface measured on mo/day/yr 6-19-00			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm; Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 8 1/2 in. to 35' ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes. No. X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
Blank casing diameter 2.375 in. to 20' ft., Dia				9 Other (specify below)	
Casing height above land surface Flush Ht. in., weight				Casing Joints: Glued. Clamped.	
TYPE OF SCREEN OR PERFORATION MATERIAL:				Welded.	
1 Steel		3 Stainless steel		Threaded. X	
2 Brass		4 Galvanized steel			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Concrete tile	
1 Continuous slot		6 Wire wrapped		CASING JOINTS: Glued. Clamped.	
3 Mill slot		7 Torch cut		Welded.	
2 Louvered shutter				Threaded. X	
4 Key punched					
SCREEN-PERFORATED INTERVALS: From 35' ft. to 20' ft., From ft. to ft.				SDR 13	
				SCH 40	
GRAVEL PACK INTERVALS: From 35' ft. to 18' ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 18' ft. to 3' ft., From 3' ft. to 0' ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
Direction from well? West				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
How many feet? 20'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Concr.			
.50	3	Sand, med-crs, sl moist, sub rounded, no odor.			
8	9	Gray clay, sl. firm, no odor.			
9	13	Clay, dk tan brn, moist, soft, silty at 13', no odor.			
13	16	Tan silty clay, soft, moist, banded, none-sl odor.			
16	25	Brn silt, soft, sl moist, friable, sl odor.			Fl mt ok'd by Don Taylor
25	35	Fine sand, sub rounded, well sorted, moist-wet at 28', no odor.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-17-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 539 This Water Well Record was completed on (mo/day/yr) 11-5-00 under the business name of JB Environmental Drilling by (signature) James Becker					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					