

1] LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: WYANDOTTE		$\frac{1}{4}$ $\frac{1}{4}$ NE $\frac{1}{4}$	17	T 11 S	R 25 EW
Distance and direction from nearest town or city street address of well if located within city? 100 SOUTH 20TH STREET, KANSAS CITY, KS					
2] WATER WELL OWNER: KANSAS NATIONAL GUARD					
RR#, St. Address, Box # : 131 SW 27TH STREET				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : TOPEKA, KS 66611-1159				Application Number: NA	
3] LOCATE WELL'S LOCATION WITH		4] DEPTH OF COMPLETED WELL: 37 ft. ELEVATION: NA			
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1. NA ft. 2. NA ft. 3. NA ft.			
		WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr NA			
		Pump test data: Well water was NA ft. after NA hours pumping NA gpm			
		Est. Yield NA gpm: Well water was NA ft. after NA hours pumping NA gpm			
		Bore Hole Diameter: NA in. to NA ft., and NA in. to NA ft.			
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 <u>Monitoring well</u>					
Was a chemical/bacteriological sample submitted to Department? Yes. No. X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No X					
5] TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS: Glued. Clamped.
<u>2 PVC</u>		4 ABS	7 Fiberglass		Welded.
Blank casing diameter 2 in. to 27 ft., Dia NA in. to NA ft., Dia NA in. to NA ft.		Threaded. X			
Casing height above land surface: NA in., weight NA lbs./ft. Wall thickness or gauge No. SCD 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		<u>3 Mill slot</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	ft.
SCREEN-PERFORATED INTERVALS: From 27 ft. to 37 ft., From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft.					
GRAVEL PACK INTERVALS: From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft.					
6] GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite CHIPS</u> Other					
Grout Intervals: From 0.5 ft. to 37 ft., From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? NA				13 Insecticide storage	NA
				How many feet? NA	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			0.0	0.5	TOP SDIL
			0.5	37	BENTONITE CHIPS
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/02/01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 601 This Water Well Record was completed on (mo/day/yr) 02/05/01 under the business name of Hydro-LOGIC, Inc by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					