

WYANDOTTE

WATER WELL RECORD

Form WWC-5

KSA 82a-1212 ID No.

MW#7

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Johnson</u>		<u>NE 1/4 SE 1/4 NW 1/4</u>	<u>22</u>	T <u>11</u> S	R <u>25</u> EW
Distance and direction from nearest town or city street address of well if located within city: <u>835 South St. Paul KS KS</u>					
2 WATER WELL OWNER: <u>Mr JH Robertson</u>					
RR#, St. Address, Box #: <u>JMC Projects INC</u>					
City, State, ZIP Code: <u>PO Box 5306 KS KS 66119</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>40</u> ft. ELEVATION:			
<div style="text-align: center;">N ---NW---NE--- X ---SW---SE--- S</div>		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>7 1/4</u> in. to <u>40</u> in. to in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No. ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. Clamped. 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2</u> in. to <u>25</u> in. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: <u>0</u> in., weight <u>Sched 40</u> lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 10 Asbestos-cement 11 Other (specify) 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 12 None used (open hole) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 2 Mill slot <u>0.10</u> 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From <u>40</u> ft. to <u>25</u> ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>40</u> ft. to <u>25</u> ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>6</u> ft. to <u>23</u> ft. From <u>23</u> ft. to <u>6</u> ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>South</u> How many feet? <u>120'</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Topsoil			
1	11	Dark silty clay			
11	16	Clayey fine sand & bentonite tan			
16	28	Fine to med sand			
		Top stained 27-28'			
28	40	Wet med to coarse sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>01-5-01</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>575</u> This Water Well Record was completed on (mo/day/yr) <u>01-25-01</u> under the business name of <u>FUNKIE DRINKING SERVICE</u> by (signature) <u>Allen L. King</u>					