WATER WELL RECORD Form WWC-5 KSA 82a-1212 Township Number Range Number 1 LOCATION OF WATER WELL: Fraction Section Number NW 1/4 9 11 25 NW 1/4 WYANDOTTE County: Distance and direction from nearest town or city street address of well if located within city? 1725 STATE AVE, KANSAS CITY, KS 2 WATER WELL OWNER: SAVAGE PHILLIPS 66 RR#, St. Address, Box # : 2010 WASHINGTON RD KSA 82a-1912 Board of Agriculture, Division of Walk Best Glde ECORD VForm WWC-5 KANSAS CITY KS Application Number: City, State, ZIP Code LOCATE WELL'S LOCATON WITH DEPTH OF COMPLETED WELL 15 ft. ELEVATION: AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 10 ft. 2 ft. 3 Ft. WELL'S STATIC WATER LEVEL 5.25 ft. below land surface measured on mo/day/yr 5/10/01 Pump test data: Well water was Ft. after hours pumping Gpm Est. Yield Gpm: Well water was Ft. after Hours pumping Gpm
Bore Hole Diameter 4.25 In. to 15 ft. and in. to Ft.
WELL WATER TO BE USED AS: 5 Public water supply
1 Domestic 3 Feed lot 6 Oil field water supply
9 Dewatering 12 Other (Specify below) 11 Injection well
12 Other (Specify below) W 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well MW-1 · SE -Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Water Well Disinfected? Yes No X CASING JOINTS: Glued Clamped 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile Welded 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Threaded X 4 ABS 2 PVC 7 Fiberglass Blank casing diameter 2 in. to In. to ft., Dia in. to ft. Casing height above land surface FLUSH in., weight SCH 40 Lbs./ft. Wall thickness or gauge No. 7 PVC 10 Asbestos-cement TYPE OF SCREEN OR PERFORATION MATERIAL: 8 RMP (SR) 11 Other (specify) 5 Fiberglass 1 Steel 3 Stainless steel 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 8 Saw cut 5 Gauzed wrapped 11 None (open hole) 3 Mill slot 9 Drilled holes 6 Wire wrapped 1 Continuous slot 10 Other (specify) 2 Louvered shutter 4 Key punched 7 Torch cut SCREEN-PERFORATED INTERVALS: From 4.5 ft. to 15 ft. From ft. to ft. 
 From
 ft. to
 ft. From
 ft. to
 Ft.

 From
 3
 ft. to
 15
 ft. From
 ft. to
 Ft.
 SAND PACK INTERVALS: ft. From 3 Bentonite 6 GROUT MATERIAL: 2 Cement grout 4 Other Neat cement Ft. Grout Intervals From 3 1 ft. to 3 From 2 1 to 10 Livestock pens What is the nearest source of possible contamination: 14 Abandoned water well 11 Fuel storage 15 Oil well/ Gas well 1 Septic tank 4 Lateral lines 7 Pit privy 12 Fertilizer storage 16 Other (specify below) 5 Cess pool 8 Sewage lagoon 2 Sewer lines **Contaminated Site** 9 Feedyard 13 Insecticide storage 6 Seepage pit 3 Watertight sewer lines How many feet? Direction from well? CODE PLUGGING INTERVALS LITHOLOGIC LOG FROM TO FROM SILTY CLAY BACKFILL 0 SILTY CLAY 10 SAND 10 15 END OF BOREHOLE 15 TD 7 | CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (x) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and w Completed on (mo/day/yr) 5/9/01 And this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 5/15/01 By (signature) Darin R Duncan Associated Environmental, Inc. under the business name of INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.