

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Wyandotte		SE ¼ SE ¼ SE ¼		18		T 11 S		R 25 (2W)	
Distance and direction from nearest town or city street address of well if located within city? 3601 Fairbanks Ave, Kansas City, Kansas ½ mile NE									
2 WATER WELL OWNER: SPX Corporation									
RR#, St. Address, Box # : 13515 Ballantyne Corporate Place						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Charlotte North Carolina 28277						Application Number:			
3 LOCATE WELL'S LOCATION WITH		4 DEPTH OF COMPLETED WELL: 45.0 ft. ELEVATION: 757.614							
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1. 40 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL: 35.76 ft. below land surface measured on mo/day/yr 6/17/05							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter. in. to ft., and in. to ft.							
		WELL WATER TO BE USED AS:							
		5 Public water supply		8 Air conditioning		11 Injection well			
		1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering	
		2 Irrigation		4 Industrial		7 Domestic (lawn & garden)		10 Monitoring well	
		Was a chemical/bacteriological sample submitted to Department? Yes. (No.); If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes (No)							
5 TYPE OF BLANK CASING USED:									
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued. Clamped.	
(2 PVC)		4 ABS		6 Asbestos-Cement		9 Other (specify below)		Welded	
				7 Fiberglass				(Threaded)	
Blank casing diameter 2 in. to 29.5 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel		3 Stainless steel		5 Fiberglass		(7 PVC)		10 Asbestos-cement	
2 Brass		4 Galvanized steel		6 Concrete tile		8 RMP (SR)		11 Other (specify)	
						9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot		(3 Mill slot)		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes			
				7 Torch cut		10 Other (specify)		ft.	
SCREEN-PERFORATED INTERVALS: From 45.0 ft. to 29.5 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 45.0 ft. to 27.5 ft., From ft. to ft.									
6 GROUT MATERIAL:									
1 Neat cement		2 Cement grout		(3 Bentonite)		4 Other			
Grout Intervals: From 27.5 ft. to 3 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank		4 Lateral lines		7 Pit privy		(10 Livestock pens)		14 Abandoned water well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		(11 Fuel storage)		15 Oil well/Gas well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage		16 Other (specify below)	
						13 Insecticide storage			
Direction from well? South-Southeast						How many feet? 600			
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0	5	Silty clay; dark brown							
5	16	Silty sand; brown; fine							
16	22	Clayey silt; gray brown							
22	34	Silty sand; brown; fine							
34	39	Sand; brown; med							
39	54	Sand; brown; med-coarse							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/25/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 614 This Water Well Record was completed on (mo/day/yr) 6/20/05 under the business name of MAXIM by (signature) W. St. John									