

**CORRECTION(S) TO WATER WELL RECORD (WWC-5)**

(to rectify lacking or incorrect information)

County: Wyandotte

Location listed as:

Location changed to:

Section-Township-Range: 2-115-25E

2-115-25E

Fraction (  $\frac{1}{4}$   $\frac{1}{4}$   $\frac{1}{4}$ ): NW NE NW

W2 NW NE NW

Other changes: Initial statements: \_\_\_\_\_

Changed to: \_\_\_\_\_

Comments: \_\_\_\_\_

verification method: Map of well locations from owner, and  
North Kansas City 1:24,000 topo. map.

initials: DRJ date: 9/15/2005

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726  
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

PZ 413


---



<b>PROJECT NUMBER</b> 321564.SI.01	<b>BORING NUMBER</b> PZ-413
SHEET 1 OF 1	
<b>SOIL BORING LOG</b>	

<b>PROJECT :</b> Conoco Phillips - Supplemental SI	<b>NORTHING:</b> 307239.61	<b>EASTING:</b> 2274642.92
<b>ELEVATION :</b> 751.83 ft b.t.o.c.	<b>DRILLING CONTRACTOR :</b> Max's Enterprises Inc.	
<b>DRILLING METHOD AND EQUIPMENT USED :</b> CME 750 Rig, HSA	<b>LOGGER :</b> C. Morris	
<b>WATER LEVELS :</b> 30' bgs	<b>START :</b> 11/05/04 1535	<b>END :</b> 1600

DEPTH BELOW SURFACE (FT)	INTERVAL (FT)	RECOVERY (FT)	#/TYPE	STANDARD PENETRATION TEST RESULTS	SOIL DESCRIPTION	COMMENTS
				6"-6"-6" (N)	SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY, OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY.	DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS, AND INSTRUMENTATION.
						Notes
					0.0': Clay and gravel fill, dark brown with gray gravel, moist, slightly firm, loose	
					4.0': Clay fill with gravel, stained gray to brown, moist, medium firm, HC odor	
5						
10						
15					14.0': Silty clay with gravel (CL), gray to brown, moist, medium firm, HC odor	
					16.0': Silty clay with gravel (CL), gray to brown, moist, medium firm, HC odor	
20					19.0': Grading moist, soft	
25					23.0': Elastic silt with sand (MH), dark gray to black, moist, soft, HC odor	
					26.0': Silty sand (SM), dark gray, moist, crumbly, poorly graded, strong HC odor	
					29.0': Grading increasing moisture, sample sticks	
					30.0': Silty sand (SM), olive gray, wet to saturated, sheen/product-iridescent, strong HC odor, high PID readings, poorly graded	
35					35.0': End of boring	

File Name:	Created By:	Date Created:	 KONTRON LLC
	E. ALEXANDER	MAR 06 2006	