

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Wyandotte

Location listed as:

Location changed to:

Section-Township-Range: 2-115-25E

2-115-25E

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): NW NW NW

E2 SW NE NW

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

verification method: Map of well locations from owner, and

North Kansas City 1:24,000 topo. map.

initials: DRK date: 9/15/2005

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.



PROJECT NUMBER 321564.SI.01	BORING NUMBER PZ-363
SHEET 1 OF 1	
SOIL BORING LOG	

PROJECT : Conoco Phillips - Supplemental SI	NORTHING: 306539.81	EASTING: 2274973.24
ELEVATION : 742.76 ft b.t.o.c.	DRILLING CONTRACTOR : Max's Enterprises Inc.	
DRILLING METHOD AND EQUIPMENT USED CME 750	LOGGER : E. Molander	
WATER LEVELS : 28' bgs	START : 11/18/04 1640	END : 11/18/04 1700

DEPTH BELOW SURFACE (FT)	INTERVAL (FT)	RECOVERY (FT)	#/TYPE	STANDARD PENETRATION TEST RESULTS 6"-6"-6" (N)	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY, OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY.	COMMENTS DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS, AND INSTRUMENTATION. <div style="text-align: right; font-size: small;">Notes</div>
					0.0': Silty clay (CL), brown, moist, firm, organic material	
					6.0': Sandy silt (ML), yellowish brown, moist, poorly graded	
					8.0': Silt (ML), brown, wet, very soft	
					10.0': Silty sand (SM), brown, moist, poorly graded, fine	
					12.0': Silty sand (SM), brown, wet, poorly graded	
					13.0': Poorly graded sand (SP), yellowish brown, moist, fine	
					26.0': Poorly graded sand with trace silt (SP), brown, very moist to wet, fine	
					28.0': Encounter water	
					32.0': Poorly graded sand with trace silt (SP), gray, wet	
					35.0': End of boring	

R25E

