			TER WELL REC	ORD For	m WWC-5	KSA 82a-	1212 ID N		5		
		TER WELL:	Fraction		a 1		tion Number		nip Number	Range Number	
	vyandot		NW 1/4	NN 1/4	NW		21	<u> </u>	N s	R 25 €W	
	nd direction 1	rom nearest tov	vn or city street a	address of we	II if located	within city?					
App	NACT ON	oc north				-					
			e-Palmolive Kansas Av	į.							
City, State,		Kanso	s City KS	66105				Applic	ation Number:	Division of Water Resources	
3 LOCATE	WELL'S LO	CATION WITH	4 DEPTH OF C	OMPLETED	WELL	37.5	ft. ELEVA	TION:			
AN "X" IN	SECTION	BOX:	Depth(s) Groun	dwater Enco	untered	137	fi	t. 2	ft. 3	11/30/05 ft.	
X	N	1	WELL'S STATIO	C WATER LE	VEL	ハランft. bek	w land surfac	ce measured o	n mo/day/yr	oumping gpm	
	1	ı	Est. Yield	apm:	Well wate	er was	ft.	after	hours p	oumping gpm	
	-NW -	- NE	WELL WATER			Public water s		8 Air conditi		njection well	
		; <u> </u>	1 Domestic			Oil field water				Other (Specify below)	
W	1	 E	2 Irrigation	4 Indus	triai /	Domestic (lav	vn & garden)	10 Monitoring	g weii		
	- 6/4/	- 65 -									
SW SE Was a chemical/bacteriological sample submitted to Department? Yes; If yes, mo/day/yrs sample water Well Disinfected? Yes No										no/day/yrs sample was sub- No	
	i	<u> </u>	mitted				VV	alei Well Disil	necteu: Tes	NO	
5 7/05/	S	1401110 11055									
1 Stee		ASING USED: 3 RMP (SI	D\	5 Wrought 6 Asbestos		8 Concre	ete tile	CASING	G JOINTS: Glue الملا	ed ded	
2 PVC		4 ABS	n) ∤	7 Fiberglas		3 Other	specify below	CPVC	Thre	eaded	
Blank casir	ng diameter	12	in. to	•						ft.	
Casing hei	ght above la							. lbs./ft. Wall th	nickness or qua	ne No. Sch Sc	
TYPE OF S	SCREEN OF	R PERFORATIO	N MATERIAL:			7 PV	_	10	Asbestos-Cer	nent COW	
				5 Fiberglas			8 RMP (SR) 9 ABS		10 Asbestos-Cement 11 Other (Specify) CPVC 12 None used (open hole)		
2 Bras	-	4 Galvaniz		6 Concrete			5		•	,	
		RATION OPENIN				zed wrapped		8 Saw cut 9 Drilled h		11 None (open hole)	
	tinuous slot vered shutte		fill slow ey punched		7 Torc	wrapped h cut				ft.	
			. From	37.5			4 F)ft.	
SCHEEN-I	PERFORATI	ED INTERVALS	: From		π. to		π., From	1 1	π. το)π.)	
(GRAVEL PAG	CK INTERVALS	: From	37.5	ft. to	29	ft., From	29	ft. to	ft.	
			From		ft. to	•••••	ft., From	າ	ft. to	oft.	
6 GBOL	T MATERIA	I: 1 Nea	t cement	2 Cemer	nt grout	3 Ben	tonite	4 Other			
Grout Inter	vals: Fron	76	ft. to	ft Fi	rom	ft. 1	0	ft From		ft. toft.	
What is the			contamination:	,			10 Lives	stock pens	14	Abandoned water well	
1 Septic tank 4 Lateral lines					7 Pit privy		11 Fuel storage		15 (15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon		12 Fertilizer storage		16 (16 Other (specify below)		
3 Wat	tertight sewe	er lines 6 Seep	page pit		9 Feedyard			13 Insecticide storage			
Direction fr	om well?						How ma	ny feet?			
FROM	то		LITHOLOGIC	CLOG		FROM	ТО		PLUGGING II	NTERVALS	
0	3	Fill									
3	3(Clay, tra	ce fine sand	dark gr	ay			-			
31	37.5	Fine sa	nd, olive	gray							
						-					
						<u> </u>					
						+					
7 CONTR	ACTORIO C	D I ANDOMASI	L'e CEPTIFICA	TION! This	untar was II	(a) (d) =====	untard (C)	onotro-to-1	(O) ml	adag as a fingle distance and a	
COMPleted (n (mo/day/	rear)(/	101 EHITFICA	TION: This w	vater well v	vas (1) constr	ucted, (2) red	constructed, or	the best of multi-	nder my jurisdiction and was	
Water Well	Contractor's	Licence No	529			r Well Record	was complet	ed on (mo/dev	/vr)	nowledge and belief. Kansas	
	usiness nan		acotaniza			1100010		(s ignature)		11.	
					T clearly Plea	se fill in blanks un		· · · · · · · · · · · · · · · · · · ·	Send ton three conic	es to Kansas Department of Health	
and Enviro	nment, Bureau		ection, 1000 SW Jacks							NER and retain one for your	