

MW-32

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Wyandotte</u>		<u>SE 1/4 SE 1/4 SE 1/4</u>	<u>18</u>	T <u>11</u> S	R <u>25</u> (EW)
Distance and direction from nearest town or city street address of well if located within city? <u>3601 Fairbanks Ave. KCKs</u> <u>800' SW</u>					
2 WATER WELL OWNER: <u>SFX Corp</u> RR#, St. Address, Box # : <u>13535 Ballantyne Corp. Place</u> City, State, ZIP Code : <u>Charlotte N. Carolina 28277</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>39.5</u> ft. ELEVATION: <u>751.60</u>			
		Depth(s) Groundwater Encountered 1. <u>35</u> ft. 2. <u>35</u> ft. 3. <u>35</u> ft. WELL'S STATIC WATER LEVEL <u>30.5</u> ft. below land surface measured on mo/day/yr <u>10/10/05</u> Pump test data: Well water was <u>35</u> ft. after <u>10/10/05</u> hours pumping <u>35</u> gpm Est. Yield <u>35</u> gpm: Well water was <u>35</u> ft. after <u>10/10/05</u> hours pumping <u>35</u> gpm Bore Hole Diameter <u>35</u> in. to <u>35</u> ft., and <u>35</u> in. to <u>35</u> ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) <u>10 Monitoring well</u> Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>No</u>			
		5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>No</u> Clamped <u>No</u> 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded <u>No</u> <u>2 PVC</u> 4 ABS 7 Fiberglass <u>Threaded</u> Blank casing diameter <u>2</u> in. to <u>29</u> ft., Dia <u>29</u> in. to <u>29</u> ft., Dia <u>29</u> in. to <u>29</u> ft. Casing height above land surface <u>FLUSH</u> in., weight <u>29</u> lbs./ft. Wall thickness or gauge No. <u>29</u>			
		TYPE OF SCREEN OR PERFORATION MATERIAL: <u>7 PVC</u> 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) <u>29</u> 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot <u>3 Mill slot</u> 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) <u>29</u> ft.			
		SCREEN-PERFORATED INTERVALS: From <u>39</u> ft. to <u>29</u> ft., From <u>29</u> ft. to <u>29</u> ft. GRAVEL PACK INTERVALS: From <u>39.5</u> ft. to <u>27</u> ft., From <u>27</u> ft. to <u>27</u> ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other <u>29</u>					
Grout Intervals: From <u>24</u> ft. to <u>2</u> ft., From <u>2</u> ft. to <u>2</u> ft., From <u>2</u> ft. to <u>2</u> ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy <u>11 Fuel storage</u> 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? <u>East</u> How many feet? <u>800' East</u>					
FROM TO LITHOLOGIC LOG			FROM TO PLUGGING INTERVALS		
0.0 0.4 asphalt					
0.4 9.0 brn cly silt-sand					
9.0 34.0 brn fine sand					
34.0 40.0 med brn sand					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-5-05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>614</u> This Water Well Record was completed on (mo/day/yr) <u>10/31/05</u> under the business name of <u>Maxim</u> by (signature) <u>William J. Jones</u>					