ì	
١	Ť
ŧ	┰
ı	$\overline{}$
ł	÷
L	"
ł	
ı	₫.
ı	П
ı	
ı	ĭ
Ł	f
ı	-
ı	
١	
١	

	WATER WELL RECORD	Form WWC-5 KSA 82	2a-1212 ID No.	
1 LOCATION OF WATER WELL:	1	Section Numi	'	Range Number
		SW 1/2 17	T 11 S	R 25 E
Distance and direction from nearest 3601 Fallbanks Ave., Kansas	town or city street address of well if locals City. Kansas	ated within city?	^	
2 WATER WELL OWNER: SPX				
	15 Rallantyne Corporate Pla	ce	Board of Agriculture Di	vision of Water Resources
Cha	riotta North Carolina 28277		Annilostian Nombon	
2 LOCATE WELL'S LOCATON WI	TH /		/ ppiloadoff (Varibo).	
AN "X" IN SECTION BOX:	TH 4 DEPTH OF COMPLETED WEL Depth(s) Groundwater Encountered	L 53 ft. E	LEVATION:	
it				
nwne	WELL'S STATIC WATER LEVEL	ft. below lar	nd surface measured on mo/day	//yr ፫፫
	Pump test data: Well	water was	ft. after hours	pumping gpm c
M Miles	E Est. Yield gpm: Well	water was	ft. after hours	pumping gpm m
i	Bore Hole Diameter 8.25 in WELL WATER TO BE USED AS: 1 Domestic 3 Feed lot	. to 55	ft. and	in. to ft. 2
SW SE	WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning	11 Injection well
x	1 Domestic 3 Feed lot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
S			estic) 10 Monitoring well	
	Was a chemical/bacteriological san			
	submitted		Water Well Disinfected? Yes	
5 TYPE OF BLANK CASING USE	D: 5 Wrought Iron	n 8 Concrete tile	CASING JOINTS: Glu	
1 Steel 3 RM	MP (SR) 6 Asbestos-Ce	ement 9 Other (specify I		
2 PVC 4 AB	3S 7 Fiberglass		Thre	aded Flush
Blank casing diameter 2	in. to 38 ft., Dia			in. to ft.
Casing height above land surface	32.4 in., weight	0.703 lbs	./ft. Wall thickness or gauge No	SCH. 40
TYPE OF SCREEN OR PERFORA		7 PVC	10 Asbestos-cen	nent
1 Steel 3 Sta	ainless steel 5 Fiberglass		R) 11 Other (specify	
	alvanized steel 6 Concrete tile	9 ABS	12 None used (o	pen hole)
SCREEN OR PERFORATION OPE	NINGS ARE: 5	Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot 6	Wire wrapped	9 Drilled holes	
2 Louvered shutter		Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVA	ALS: From 38 ft. to	53	ft. From ft	. toft.
	From ft. to			
GRAVEL PACK INTERVAL	00.4	- 55	ft. From ft	. to ft.
,	From ft. to			. to ft.
6 GROUT MATERIAL: 1 No	eat cement 2 Cement grout	3 Bentonite	4 Other	
Grout Intervals From 36.1	ft. to 1 ft. From	ft to	ft From	ft to ft
What is the nearest source of possi	ble contamination:	10 1	ivestock pens 14 A	bandoned water well
	4 Lateral lines 7 Pit			oil well/ Gas well
2 Sewer lines				ther (specify below)
3 Watertight sewer lines	-		nsecticide storage	
Direction from well?		How m	nany feet?	
FROM TO CODE	LITHOLOGIC LOG	FROM TO	PLUGGING	INTERVALS
	Sandy Clay, brown	101		
	Silty Sand, brown, fine			SEC.
43.5 53.5	Silty Sand, gray brown, fine			
53.5 55	Sand, gray brown, medcoa	arse		
		-		
		-		
7 CONTRACTOR'S OR LANDOW	NER'S CERTIFICATION: This water w	ell was (1) constructed, (2)	reconstructed, or (3) plugged ur	der my jurisdiction and was
	7/25/06		is true to the best of my knowl	!
Water Well Contractor's License No			ell Recount was completed on (f)	
under the business name of	Geotechnical Services		ure) Just limst	
INSTRUCTIONS: Please fill in b	planks and circle the correct answers. Send	three copies to Kansas Depa	rtment of Health and Environment,	Bureau of Water, 1000 S W
Jackson St., Ste. 420, Topeka, K	ansas 66612-1367. Telephone: 913-296-5	545. Send one to WATER W	ELL OWNER and retain one for yo	ur records.