6MW-3A

WATER WELL	RECORD	Form WWC-5	Division of V	Vater Resources; App. No		
1 LOCATION OF	WATER WELL:	Fraction .	Section Number			
County: Wyan doffe		SE 1/4 NW 1/4 SE 1/4	19	T II S	R 25 1 W	
1 LOCATION OF WATER WELL: County: Wyan dotte Distance and direction from nearest town or city street address of well if Global Positioning Systems (decimal degrees, min. of 4 digits)						
located within city	Fr IF court of Aco	att Klud & 42 nd C+		N 39° 4.778		
CATX Facility: NE corne of Argentine Blood: 42nd St. 2 WATER WELL OWNER: 6 MTX Rail Corporation RR#, St. Address, Box #: 500 west Monroe Street Latitude: 10 39 9.118 Longitude: W 940 40. 466 Elevation: 769 Nad \$3						
RR#, St. Address	Box# : Soo West	Monroe Street	Elevation:	769		
City, State, ZIP (Code : Chicago,		Data Collection			
3 LOCATE WELI			Data Concert			
LOCATION						
WITH AN "X" I						
SECTION BOX						
N	N Pump test data: Well water was					
	WELL WATER TO BE LICED AC. 5 Public water cumply 9 Air conditioning 11 Injection well					
WELL WATER TO BE USED AS. 3 Fublic water supply NET TO BE USED AS. 3 Fublic water supply NET To BE USED AS. 3 Fublic water supply NET TO BE USED AS. 3 Fublic water supply NET TO BE USED AS. 3 Fu						
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well						
Sample was submitted						
S						
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped						
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded						
PVC 4 ABS 7 Fiberglass Threaded						
Casing height above land surface. Flushmant. in., Weight						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless Steel 5 Fiberglass OPVC 9 ABS 11 Other (Specify)						
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot						
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From						
From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From40						
From						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From .73 ft. to .7 ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage (6) ther (specify						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well P. Shaham Direction from well? How many feet?						
FROM TO	LITHOLOGI		OM TO	PLUGGING IN		
	Garel Debris	230		120001101	TER TIES	
	Sity Clay, Black	4				
10 40	Time sand grading to	Coarse Sanel				
·						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged						
under my jurisdiction and was completed on (mo/day/year) [2.1.13] and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No						
under the business n	name of Below board Surf	W, Tru	by (signature)			
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline of circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone						
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at						