

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Wyandotte</u>		<u>SE 1/4 SE 1/4 SE 1/4</u>	<u>18</u>	<u>T 11 S</u>	<u>R 25 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>3601 Fairbanks Ave. KCKS 600 N</u>					
2 WATER WELL OWNER:		RR#, St. Address, Box #		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code		<u>SPX Corp. Ballintyne Corp. Place</u> <u>13535 Charlotte N. Carolina</u>		Application Number: <u>28277</u>	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>48</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>41</u> ft. 2. <u>41</u> ft. 3. <u>41</u> ft.			
		WELL'S STATIC WATER LEVEL <u>40.7</u> ft. below land surface measured on mo/day/yr <u>11-28-06</u>			
		Pump test data: Well water was <u>41</u> ft. after <u>41</u> hours pumping <u>41</u> gpm			
		Est. Yield <u>41</u> gpm: Well water was <u>41</u> ft. after <u>41</u> hours pumping <u>41</u> gpm			
		Bore Hole Diameter: <u>8 1/4</u> in. to <u>49</u> ft., and <u>49</u> in. to <u>49</u> ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>0 Monitoring well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes <u> </u> No <u> </u> ; If yes, mo/day/yr sample was submitted <u> </u>			
		Water Well Disinfected? Yes <u> </u> No <u>X</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u> </u> Clamped <u> </u> <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u> </u> Blank casing diameter <u>2</u> in. to <u>32.5</u> ft., Dia <u> </u> in. to <u> </u> ft., Dia <u> </u> in. to <u> </u> ft. Casing height above land surface <u>none</u> in., weight <u> </u> lbs./ft. Wall thickness or gauge No. <u>sch 80</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) <u> </u> SCREEN OR PERFORATION OPENINGS ARE: 12 None used (open hole)					
1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From <u>48.0</u> ft. to <u>32.5</u> ft., From <u> </u> ft. to <u> </u> ft. GRAVEL PACK INTERVALS: From <u>48.0</u> ft. to <u>29.5</u> ft., From <u> </u> ft. to <u> </u> ft.					
6 GROUT MATERIAL: 1 Neat cement <u>2 Cement grout</u> <u>3 Bentonite</u> 4 Other <u> </u>					
Grout Intervals: From <u>24.5</u> ft. to <u>1.0</u> ft., From <u>29.5</u> ft. to <u>25</u> ft., From <u> </u> ft. to <u> </u> ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon <u>11 Fuel storage</u> 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? <u>800' South</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	1.0	grass cover, Top soil			
1.0	15.0	brn sandy clay silt			
15.0	20.0	brn silty sand			
20.0	25.0	brn Fine med sand			
25.0	32.0	brn to gry brn med sand			
32.0	49.0	wet gry brn sand @ 41'			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11/28/06</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>614</u> This Water Well Record was completed on (mo/day/yr) <u>6/28/06</u> under the business name of <u>MAXIM TECHNOLOGIES</u> by (signature) <u>William Stafford</u>					