WATE	R WELI	RECORD MW	Form WW	C-5	Division of Wate	er Resources; App. No.		
		of Water Well: ndotte	Fraction NE 1/4 NW 1/4	VW 1/4	Section Number	Township Number T // S	Range Number R W	
Dieta	nce and di	rection from nearest town or				g Systems (decimal deg		
					T - 434 1	g ~ J ~ · · · · · · · · · · · · · · · · ·		
512	Corner	of Fairboy Trawa	Quirdare Blue					
2 WA	TER WEI	I OWNED.	111:11					
RR#	, St. Addre	ess, Box # : /234 ///	my ponumy	1	Datum:			
	, State, ZII	Code : Rayla 3/1	K, OK 74804		Data Collection	Method:		
2 100	TATE WE		MPLETED WELL		ft.			
LOCATION								
	WITH AN "X" IN Depth(s) Groundwater Encountered (1)							
	SECTION BOX: WELL'S STATIC WATER LEVEL6.15 ft. below land surface measured on mo/day/yr. 7-12-0.7.							
520	N Pump test data: Well water wasft. after hours pumping gpm							
□ X 1	Est. Yieldgpm: Well water wasft. afterhours pumpinggpm							
"	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 12 Other (Specific below)							
WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feedlot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below) 12 Other (Specify below)								
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well								
was a chemical/bacteriological sample submitted to Department? Yes								
Sample was submitted								
S								
5 TYPI	E OF CAS	ING USED: 5 Wrough	ht Iron 8 Co	oncrete tile	CASIN	G JOINTS: Glued		
L	Steel	3 RMP (SR) 6 Asbest	os-Cement 9 Ot	her (specify l	pelow)	Welded		
(2)	₽VC	4 ABS 7 Fibergl	ass			Threaded	X	
Casing height above land surface. 30 in., Weight lbs./ft. Wall thickness or guage No. 40 10 10 10 10 10 10 10								
Casing height above land surface30								
		N OR PERFORATION MA	TERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass OPVC 9 ABS 11 Other (Specify)								
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)								
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From ft. to ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From 20 ft. to 4 ft., From ft. to ft.								
From								
	UT MATI							
Grout Intervals: From								
What is the nearest source of possible contamination:								
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage (16 other (specify								
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well Direction from well? How many feet?								
		LITHOLOG	TC LOC	FROM	TO		CDVALC	
FROM	TO	CIII CLOO	il Lou	FROM	10	PLUGGING INTI	ERVALS	
0_		STIFF Clay with TIL	paterial CC					
	70	Sandy Clay, wet	Brown, Soft		-			
					 			
				-				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, (2) reconstructed, or (3) plugged								
under my jurisdiction and was completed on (mo/day/year)								
Kansas Water Well Contractor's License No								
under the business name of Below Ground Surface by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top								
three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone								
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								