WATE	R WELL	RECORD	For	n WWC-5	, D	ivision of W	ater Reso	ources: App. No.		
1 LOCATION OF WATER WELL:			Fraction	or.		Section N	lumber	Township Number	Range Number	
Distance a	nd directio	vandotte	SW 1/4	SE 4	SW 1/4	Clohal Da	-i+!:	T 11 S	R 25 E	
County: Wyandotte SW & SE & SW & 16 T 11 S R 25 E  Distance and direction from nearest town or city street address of well if located within city? 1274 Kansas Ave., Kansas City, KS Latitude: N 39.08753°										
Longitude: W 94 64361°										
2 WATER WELL OWNER: Armourdale Muffler Shop Elevation: Pin: 751.70 TOC: 751.48										
RR#, S	St. Address,	Box # : 5350 S	wartz	•		Datum:	abov	e mean sea level		
City. S	City State ZIP Code Kansas City KS 66106 Data Collection Method: Jegal survey									
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 44.0 ft.										
LOCA	TON					MW12R				
WITH	WITH AN "X" IN Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.									
WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 31.70 ft. below land surface measured on mo/day/yr 1/24/08										
N Pump test data: Well water was ft. after hours pumping gpm										
Est. Yield gpm: Well water was ft. after hours pumping gpm										
-NW	NW NE WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
	1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
W	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10) Monitoring well									
⊢sw	- sw sE									
×	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs									
Sample was submitted Water Well Disinfected? Yes No X										
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped										
5 FIFE OF CASING USED: 5 Wrought from 8 Concrete tile CASING JOINTS: Glued Clamped										
(2) DV	1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded									
2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 24 ft., Dia in. to ft., Dia in. to ft.  Casing height below land surface 0.22 ft., Weight lbs./ft. Wall thickness or gauge No.										
Biank casing diameter 2 in to 24 ft., Dia in to ft., Dia in to ft.										
Casing height below land surface 0.22 ft., Weight lbs./ft. Wall thickness or gauge No.										
1 YPE OF SCREEN OR PERFORATION MATERIAL:										
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)										
1 Continuous slot (3) Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  SCREEN-PERFORATED INTERVALS: From 24 ft. to 44 ft. From ft. to ft.										
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From 24 ft. to 44 ft. From ft. to ft.										
From It. to It. From It. to It.										
GRAVEL PACK INTERVALS: From 23 ft. to 44 ft. From ft. to ft.										
From ft. to ft. From ft. to ft.										
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other cement, 0-2 feet										
Grout Intervals From 2 ft. to 23 ft. From ft. to ft. From ft. to ft.										
What is the nearest source of possible contamination:										
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify										
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below)										
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well										
Direction	from well?	Southwest			How man	ny feet? ~2	250 feet			
FROM	TO	LITHO	LOGIC LO	G	FRO	A TO	T	PLUGGING INTE	RVALS	
0	0.5	Asphalt	20010 00		T.KO.			1 Bedding in the	JK T T B B	
0.5	5	Sand with clay, bro	wn, verv fi	ne grained.						
		moist, no odor								
5	12	Sand with clay, bro	wn, very fi	ne grained.						
		wet, no odor								
12	37	Sand. medium grain		(tan), moist,						
22	4.5	no odor, moderately								
37	45	Sand, coarse graine		an), moist.			Floobe	a a un faus in a un fra ma D	VOW.	
		no odor, poorly sort	cu		+		riusnn	nount waiver from B	O VV	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed. (2) reconstructed. or (3) plugged										
under my jurisdiction and was completed on (mo/day/year) 1/24/08 and this record is true to the best of my knowledge and belief.										
Kansas Wa	Kansas Water Well Contractor's License No. 757 . This Water Well Record was completed on (mo/day/year) 2/12/08									
		of Larsen & Asso				ature)	The			
INSTRUCT	IONS: Plance	till in blanks or circle th	a correct auci	vers Canditon t	bree conia	to Kaneae D	epartment	of Health and Environment	. Bureau of Water.	
Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Sendone to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.										
your records.	100 0131 00	ioi eacii constructed wel	i. visit us at	nup. www.kum	CKS. EUV. W	ice well.				