WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL:	Fraction	Section Number Township No. Range Number
	SW14 SW14 SW14 SW14	6 T 11 S R 25 X E □W
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here		
from nearest town or intersection: If at owner's address, check here . Latitude:39.//.685		
4626 STATE AVE. Long		Longitude:
KANSAS CITY. KS 66102 Elevation: MWGS 84 I NAD 83 I NAD 27		
2 WATER WELL OWNER: ATLANTIC RECHFIELD CO.		Datum: WGS 84, NAD 83, NAD 27 Collection Method:
RR#, Street Address, Box #: 2240 BLUESTONE DR.		GPS unit (Make/Model:)
City, State, ZIP Code : QT. A.HA	RIES MO 63303	Digital Map/Photo, Topographic Map, Land Survey
208# 090007 - AR D/GT-2> FORMER AMOCO # 2/56 Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m		
3 LOCATE WELL	COMPLETED WELL 43	
SECTION BOX: Depth(s) Ground	water Encountered (1)	ft. (2) ft. (3) ft.
WELL'S STATIC WATER LEVEL 1.6 3 ft. below land surface measured on mo/day/yr. 6/17/59 Pump test data: Well water was		
l l l l l l l l l l l l l l l l l l l		
		ft. after hours pumping gpm
	TO BE USED AS: Public water	t., andin. toft. er supply
□ □ □ □ Domestic		r supply Dewatering Other (Specify below)
SW SE I Frigation	☐ Industrial ☐ Domestic-law	on & garden Monitoring well M.W.= 21.8
	bacteriological sample submitted to	Denartment? Ves No
	day/yr sample was submitted	
Water well disin	fected? Yes No	
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter		
Casing height above land surface		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
Steel Stainless Steel PVC Other (Specify)		
Brass Galvanized Steel None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)		
Louvered shutter		
FILLERSAND From ft. to ft., From ft. to ft.		
FRAVEL PACK INTERVALS: From 4.3 ft. to 31 ft., From ft. to ft.		
From		
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other. H.S. BENTONIE SCURRY.		
Grout Intervals: From		
□ Septic tank □ Lateral lines □ Pit privy □ Livestock pens □ Insecticide storage □ Other (specify below)		
Sewer lines Cesspool	Sewage lagoon Fuel storage	Abandoned water well
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well .		
Direction from well (O.M STATE)	Distance f	rom well (ON STIE)
FROM TO LITHOLOG	IC LOG FROM	TO LITTIO: LOG (cont.) or PLUGGING INTERVALS
0 3" GRASS/TOPSOIL		1' CANCRETE PAD N/8" F.M.
3" 27.5' SLETY CLAY W/	SOME GRAVEL	WELL PROTECTOR
27.5' 31' LIMESTONE		
31' 43' WEATHERED SH	PLE	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ⊠ constructed, ☐ reconstructed, or ☐ plugged		
under my jurisdiction and was completed on (mo/day/year)		
Kansas Water Well Contractor's License No		
under the business name of ROBERTS. ENV: DRILLING, INC. by (signature)		
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.		
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		
http://www.kdheks.gov/waterwell/index.html.		
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy		