1 LOCATIO	1 LOCATION OF WATER WELL:			Fraction			on Number	Townshin	Township Number		ge Number	
			1/4	NE v	NE		27	T 11		R	`	
Distance and	direction fron	nearest to	wn or city street ac	dress of well i	f located wit	hin city?						7
			d, between 29 ^t			ansas Cit	y					
			n Pacific Railr		oany							
RR#, St. Add	ress, Box #	: 1416	Dodge Street					Board of A	griculture, Divi	ision of Wa	ater Resource	s
City, State, Z	IP Code	: Omal	na, Nebraska	68179				Application	Number:			
3 LOCATE	WELL'S LOCA	ATON WITI	4 DEPTH OF	OMDI ETED	WELL	13	# FLEV	/ATION:				
7^\\ ^ \\	SECTION BO		Depth(s) Ground									:
	; 	X										
 	-NW	NE	WELL'S STATIO									f
# W		; } ,	Pum	ip test data:	water v	vas	,	t. after	nours p	oumping	gpr	n d n d
÷ ''	<u> </u>	·	Est. Yield	gpm:	vveli water v	vas	T	ι. aπer	nours p	oumping	gpr	n ;
	-sw	¢	Bore Hole Diam	eter 0.23	in. to	lic water su	innly	tt. and	itioning 1	1. to 1. Injection	1	ft.
	: Svv I	;	WELL WATER 1 Domesti	c 3 Feed lo	t 6 Oil	field water s	supply	9 Dewater	ing 1	2 Other (S	Specify below	0
↓ 		į						c) 10 Monito				
	S		Was a chemical									
			submitted	rbacteriologica	ii sairipie su	Dimitted to L		iter Well Disinfe			No X	
5 TYPE OF	BLANK CAS	NC USED	· · · · · · · · · · · · · · · · · · ·	5 Mraugh	t Iron	8 Concre	ete tile		OINTS: Glue			\dashv
1 Stee									Weld		Clampeu	
		_	(SR)				specify belo				Elizab	\dashv
2 PVC		4 ABS		7 Fibergla	ass				Threa	ded	riusn	_
Blank casing	diameter	2	in. to3	ft., Dia	·	in. to	0	ft., Dia		_in. to		it.
Casing heigh	nt above land	surface	Flush	in., weight	0	.703		Wall thickness			CH. 40	
TYPE OF SO	CREEN OR PI	ERFORATI	ON MATERIAL:				PVC		sbestos-ceme			
1 Stee						8	RMP (SR)	11 C	ther (specify)			
2 Bras				6 Concre			ABS	12 N	lone used (op	en hole)	. /	
	R PERFORAT	_				d wrapped		8 Saw cut		11 None	e (open noie)	
	itinuous slot	_	Mill slot		6 Wire w	• •		9 Drilled ho				
	vered shutter		Key punched		7 Torch			10 Other (sp	pecity)			
SCREEN-PE	ERFORATED	INTERVAL						rom				
			From	25	t. to	42		rom	tt.	to		tt.
GRA	AVEL PACK IN	ITERVALS						From				
.								From				ft.
			t cement 2									
Grout Interva	als From	1	ft. to 2.5	ft. From		ft. t				ft. to		ft.
What is the r	nearest source	of possible	e contamination:					tock pens	14 At	oandoned v	water well	
	tic tank		4 Lateral lines					storage		I well/ Gas		
	ver lines		5 Cess pool		Sewage I	J		izer storage	16 Ot	ther (speci	fy below)	
	tertight sewer	lines	6 Seepage pit	: 9) Feedyard			cticide storage				
Direction from		CODE	LITUO	LOGIC LOG		FROM	How many		DILICONICI	NITEDY (AL		_
FROM 0.0	1.0		ill, road gravel	LOGIC LOG		FROM	10		PLUGGING I	NIERVAL	5	-
0.0	1.0		and, poorly gra	aded fine to	medium							\dashv
1.0	13.0		rained, trace gra		cara							
		ľ										
						ļ						
						ļ						_
							-					_
						_	-					\dashv
		- 1				-						
						1						
										,		
7 CONTRA	ACTOR'S OP	LANDOWN	IER'S CERTIFICAT	TION: This was	ter well was	(1) constru	ted (2) rec	onstructed or (3	nlugged und	ler my jurio	diction and	36
			IER'S CERTIFICAT									
 completed o	n (mo/day/yr)		04/2	21/09		and th	is record is	true to the best	of my mowle	dge and b	elief. Kansas	,
completed o	n (mo/day/yr)	icense No.		21/09 531		and th	is record is	true to the best	of my mowle	dge and b	elief. Kansas	,