THE PERSON	. D	F 11	WC F	District CWI-	D Aim N	VMP-1S	
WATER WELL RECOR		Form W	WC-5		er Resources App. N	Range Number	
1 LOCATION OF WATER WELL:		Fraction	V 1/4 1/4	Section Number 20	Township No.	R 25 ZE W	
County: Wyandotte		NW 1/4 NW 1/4 NV					
Street/Rural Address of We		Global Positioning System (GPS) information:  Latitude: .30.0874 .39.0874 (in decimal degrees)					
from nearest town or intersection: If at owner's address, check here .				Longitude: 94.6671 (in decimal degrees)			
3401 Fairbanks Avenue Kansas City, KS 66106				Elevation: (In decimal degrees)			
				Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Sinclair Transportation Company				Collection Method:			
RR#, Street Address, Box #: P.O. Box 30825				GPS unit (Make/Model: Garmin 12			
City, State, ZIP Code	e City, UT 84130-0	825	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
		Est. Accuracy:	<3 m, 🔲 3-5 m, 🔽	5-15 m,  >15 m			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 13.0' ft.							
SECTION BOX: Dep	BOX: Depth(s) Groundwater Encountered (1)						
WE WE	WELL'S STATIC WATER LEVEL						
Pump test data: Well water was							
EST. YIELDgpm. Well water was							
W Bore Hole Diameter 3.25' in. to .13.0' ft., and in. to							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well  Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Vapor Point							
s		day/yr sample was su			165 110		
, -				•••••			
water wen disinfected: 1 165 Mg 140							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter 1. in. to							
			t	lbs./ft., Wall thi	ckness or gauge N	oSVII.4V	
TYPE OF SCREEN OR PERI				04 (0 10)			
☐ Steel ☐ Stainless Steel							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From 8.0' ft. to 13.0' ft., From ft. to ft.							
From							
GRAVEL PACK IN	ΓERVALS:	From. 7.0'	ft. to 13.0'	ft., From .	ft.	to ft.	
From							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From .1.0	ft. to	7.0 ft., Fron	n	ft. to ft.	From	ft. toft.	
What is the nearest source of possible contamination:							
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)							
	Cesspool	Sewage lagoon	Fuel storage				
☐ Watertight sewer lines	Seepage p	it [] Feedyard	Fertilizer st				
Direction from well South				from well1500'		CODIO NITERNALO	
	LITHOLOG		FROM	TO LITHO. L	OG (cont.) or PLU	GGING INTERVALS	
		Brown, Dry	ļ				
		rown, Damp	ļ				
6' 10' Silt, Trace C			ļ				
10' 13' Silt, Vy Dk	Grey, Damp	Fine Grain	1				
			<del> </del>				
			1		Luna		
			1				
			ļ <b>.</b>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .7/28/99 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor	's License N	o606 This V	Water Well Re	ecord was complete	on (morgay/year)	.9/29//09	
under the business name of PSA Environmental by (signature)							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
(white, blue, pink) to Kansas Departi Telephone 785-296-5522. Send one	ment of Health	and Environment, Bureau	of Water, Geolo	gy Section, 1000 SW Ja	ckson St., Suite 420,	Topeka, Kansas 66612-1367.	
http://www.kdheks.gov/waterwell/inde		EK WELL OWNER and	retain one for y	our records. Include <u>re</u>	e or \$5.00 for each c	Onsuluciou wen. Visit us at	
KSA 82a-1212 Check White Copy, Blue Copy, Pink Copy							
				/' LAJ /'			