WATI	ER WEI	L RECORD	Form W	WC-5	Division of W	ater Resources App. 1	No	
		OF WATER WELL:	Fraction		Section Numbe	1	Range Number	
	inty: Wva		1/4 SE 1/4 NW		19	T 11 S	R 25	
	Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here							
	GATX Facility located at NE Corner of Argentine Blvd. & 42nd St. in					Longitude: 94.6752 (in decimal degrees)		
	Kansas City, KS					Elevation: 768		
						Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27 Collection Method:		
	RR#, Street Address, Box #: 222 West Adams Street					☐ GPS unit (Make/Model: Garmin 60		
City, State, ZIP Code : Chicago, IL 60606-3677					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
Est. Accuracy: ☐ <3 m, ✓ 3-5 m, ☐ 5-15 m, ☐ >15 m								
1	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 20.5 ft.							
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1).16							
	WELL'S STATIC WATER LEVEL. NMft. below land surface measured on mo/day/yr							
	Pump test data: Well water was							
w  1	1 20 5 0 1							
-	WELL WATER TO BE USED AS:							
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well								
S If yes, mo/day/yr sample was submitted.								
1 mile  Water well disinfected? ☐ Yes ☑ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .2								
Casing height above land surface. Flush in., Weight								
Steel Stainless Steel PVC Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot   ☑ Mill slot   ☐ Gauze wrapped   ☐ Torch cut   ☐ Drilled holes   ☐ None (open hole)   ☐ Louvered shutter   ☐ Key punched   ☐ Wire wrapped   ☐ Saw cut   ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From20.5								
From. 7								
From								
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ✓ Bentonite ✓ Other Concrete								
Grout	Intervals:	From .3.5 ft. to	1	ı .1	ft. to .0	ft., From	ft. toft.	
1 _	_	est source of possible conta		□ Livoata alva	one     Ingestio	ida damaa 🖬 🖸	than (ama sife, balance)	
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ RR Yard								
		n well					LICCINC INTERVALS	
FROM 0	1 TO 2	LITHOLOG Gravel	IC LUG	FROM	TO LITHO.	LOG (cont.) or PL	UGGING INTERVALS	
2	8	Silty Clay						
8	20.5	Sand, Fine Grain						
-								
7.00	TD A CT	ODIC OD LANDOWNER	O CEDTIEICATIO	N. This wat-	r well was [7]	estructed 🗆	trusted or Dalicaced	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ☐ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) .5/5/11								
Kansas Water Well Contractor's License No. 7.10 This Water Well Record was completed on (mo/day/year) 6/2/11								
under the business name of Below Ground Surface, Inc. by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telepho	ne 785-296-	5522. Send one copy to WAT						
		ov/waterwell/index.html.			Check N	White Copy, B	lue Copy, Pink Copy	
KSA 82	a-1212				CHCCK.	тик сору, 🔲 в	lue Copy, L Pink Copy	