WATER WELL RECORD	Form WV	VC-5	Division of Water	r Resources App. No	
1 LOCATION OF WATER WELL:	Fraction		Section Number		Range Number
County: Wyardatte	SE 14 NW14 SE	1/4 500 1/4	2D	T // S	R Ã5 ∑ E □W
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:					
from nearest town or intersection: If at owner's address, check here . Latitude: 31.07553					
Kancan Marke			Elevation: 153,22		
2 WATER WELL OWNER: While BCD			<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27		
Kansao tily Ks. 2 WATER WELL OWNER: RR#, Street Address, Box #: City, State, ZIP Code: KDHE-BER 1000 SW Jackson			Collection Method: GPS unit (Make/Model:)		
City, State, ZIP Code : 1500 State Soll			☐ Digital Map/Photo, ☐ Topographic Map, ⚠ Land Survey		
Topaka, K5. Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m					
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL .55					
SECTION BOX: Depth(s) Groundwater Encountered (1) 1. 1. ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 1. 18 ft. below land surface measured on mo/day/yr. 1. 1. 1. ft.					
Pump test data: Well water was					
W - NW - NE - EST. YIELD gpm. Well water was ft. after hours pumping gpm Bore Hole Diameter					
W E Bore Hole Diameter					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
SWSE Domestic Feedlot Domestic Bewatering Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? Yes No					
S If yes, mo/day/yr sample was submitted					
water went distincted: 1 Tes 21 No					
5 TYPE OF CASING USED: Steel YPVC Other Other CASING IOINTS: Gland Clamped Welded Threaded					
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to ft., Diameter ft., D					
Casing height above land surface. Fush II. in., Weight					
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel VPVC Other (Specify)					
Brass Galvanized Steel None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Gother (specify)					
□ Louvered shutter □ Key punched □ Wire wrapped □ Saw cut □ Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft. from ft. ft.					
From					
From					
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☒ Bentonite ☒ Other CONCLUDE					
Grout Intervals: From		ft	. to b ft.,	From	. ft. toft.
What is the nearest source of possible conta		Livestock pe	ns 🔲 Insecticide	storage	er (specify below)
Sewer lines Cesspool	Sewage lagoon	Fuel storage	Abandoned	l water well	or (choose)
Watertight sewer lines Seepage p	it Feedyard	Fertilizer stor	rage Ll Oil well/ga om well l D	is well	
FROM TO LITHOLOG	IC LOG			OG (cont.) or PLU	GGING INTERVALS
0 3.0 DKBLODITUE	lay whoother		day fun		
3.0 7.0 Mege Bir Chay to sitty clay, fun, 4000					
7.D 10.5 & Bu situel	My 10080, 40		0.00		
10.5 16.0 DK-Med Bto U	Tu 3000 in 50	100,00			
22.0 35.0 Pul Haytin	Signer Sar				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION; This water well was a constructed, \Box reconstructed, or \Box plugged					
under my jurisdiction and was completed on (mo/day/year)					
Kansas Water Well Contractor's License No. 132 This Water Well Record was completed on (mo/day/year)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health Telephone 785-296-5522. Send one copy to WAT					
http://www.kdheks.gov/waterwell/index.html.	O ITTIDIC WILL I			<u>_</u>	TION WOUL
KSA 82a-1212					