LOCATIO	N OF WATER	R WELL:	Fraction	TVILLETILOOT	1011111	Sect	ion Number	r Tow	nship Numb	er F	Range Num	ber
County:	Wyan	dotte	SW 1/4	NE 14	NE 1/4		33	т	11	S R	25	E
istance and	direction from	n nearest tow	vn or city street add									
	erree – Kar						***					
			aters of Amer									
IR#, St. Add	ress, Box#	: PU BO	x 2328 / 6949	5 Lasso					•	re, Division of	Water Re	sources
ity, State, Z	IP Code WELL'S LOC	ATON WITH	s, OR 97759					Applic	ation Number	er:		
AN "X" IN	SECTION BO	OX:	4 DEPTH OF C	OMPLETED W	ELL	19	ft. ELE	VATION:		798.53 (1	roc)	
	i 1		pepin(s) dround	valer Encounte	reu i			II, Z				'' _
	NW	. N⊏	WELL'S STATIC	WATER LEVE	8.88	ft.	below TOC	measured	on mo/day/y	/r	03/10/	12 5
n			Pump	test data: We	ell water was			ft. after		nours pumpin	g	gpm s
) E W		E	Est. Yield	gpm: W	ell water was			ft. after	l	nours pumpin	g	gpm ř
			Bore Hole Diame WELL WATER To 1 Domestic	ter 10.25	in. to	19)	ft. and		in. to	ntion wall	ft.
	· SW	SE	1 Domestic	3 Feed lot	6 Oil field	water si d water :	uppiy supply	9 De	conditioning watering	12 Othe	er (Specify	below)
			2 Irrigation	4 Industrial	7 Lawn a	and gard	den (domest	tic) 10 M	onitoring we			
	S		Was a chemical/l									- 1
			submitted	g						Yes	* *	
TYPE OF	BLANK CAS	ING USED:		5 Wrought I	ron 8	Concr				: Glued		ed
1 Stee	el	3 RMP	(SR)							Welded		
2 PVC		4 ABS		7 Fiberglass	3					Threaded	Flu	sh
Blank casing	diameter	4	in. to 9	ft., Dia		in. 1	to	ft Dia		in. to		ft.
Casing heigh	nt above land	surface	O MATERIAL:	in., weight	0.70	3	lbs./ft	. Wall thick	rness or gau	ige No.	SCH.	40
YPE OF SO	CREEN OR P		A A SAIL A LIMIT COLUMN			7	PVC		10 Asbesto	s-cement		
1 Stee		3 Stainl	ess steel	5 Fiberglass	3	8	RMP (SR)		11 Other (s	pecify)		
2 Bras			unized steel			9	ABS	0 Cau		ed (open hole		, holo)
	R PERFORAT Itinuous slot	100000000	Mill slot		Gauzed wr Wire wrapp				ed holes	11 1	votie (obei	(Tible)
			Key punched	CONT. COLUMN ASSESSMENT ASSESSMEN	Torch cut							
	ERFORATED			9 ft. 1			ft.	From	o. (op-oy)	ft. to		ft.
			From	ft.	to		ft.	From		ft. to		ft.
GRA	VEL PACK II	NTERVALS:	From	8 ft.	to	19	ft.	From		ft. to		ft.
			From		to		ft.	From	····	ft. to		
6 GROUT I	MATERIAL:	1 Neat	cement 2	Cement grout		3 Ber	ntonite	4 Other				
Grout Interva	als From	1	ft. to 8	ft. From		ft.	to	ft.	From	ft.	to	ft.
		•	contamination:							14 Abandon		vell
	otic tank						11 Fue	storage		15 Oil well/		
	ver lines tertight sewer		5 Cess pool6 Seepage pit		Sewage lago Feedyard	on		tilizer stora ecticide sto		16 Other (sp	pecity belo	w)
Direction fro	Ū	IIIICS	o Geepage pit	9	i eeuyaiu		How mar		age			
FROM	TO	CODE		OGIC LOG		FROM	TO	19 1001.	PLUG	GING INTER	VALS	
0	0.33		sphalt_									
0.33	0.67		oncrete									
0.67	19		lay , with silt, da ay to dark gray	rk brown to b	rown							
0.01		9.	dy to durk gray									***************************************
										···		
							-	-				
	<u></u>			······································				GPS:				
									de: 39.05	6111		
								Longit	tude: -94	.631944		
7 CONTRA	ACTOR'S OR	LANDOWN	ER'S CERTIFICAT		r well was (1)							- 1
	on (mo/day/yr)		04/0	4/12						knowledge ar		
	Contractor's L			531				211		on (mo/day/)		U5/12
under the bi	usiness name	of	Geotechnic nks and circle the cor			b to Var	y (signature	e) (///		MANUALLE BURGOU		100 5 14/
Jackso	n St., Ste. 420.	topeka. Kans	nks and circle the col sas 66612-1367. Te	lephone: 913-29	6-5545. Send	one to V	vater Wel	L OWNER a	nd retain one	for your record	ds.	JOO O W