MW24

WATER WELL RECOR		WWC-5		r Resources App. No	o. L
1 LOCATION OF WATER County: Wy County	WELL: Fraction 1/4 1/4	1/4 NE 1/4	Section Number	Township No. T S	Range Number R <b>25 </b> ★E □W
Street/Rural Address of Well Location; if unknown, distance & direction			Global Positioning	System (GPS) in	formation:
from nearest town or intersection: If at owner's address, check here  Fairbanks Moise Plant			Latitude: 39.05.01.2 (in decimal degrees)  Longitude 94.40.05.5 (in decimal degrees)		
3601 Fallbanks Aue; Kansas City, Ks.			Elevation:		
2 WATER WELL OWNER: SPY COLONIATION - FMPC			Collection Method:		
2 WATER WELL OWNER: SPY Exposition - FMPC  RR#, Street Address, Box #: 13515 Ballanty of Corp. Place Green (Make/Model: Surio Etlex.  City State 7IP Code Green (Make/Model: Surio Etlex.)  Digital Man (Photo Green Hong)					
City, State, ZIP Code	Charlotte, NC	28277	☐ Digital Map/Ph Est. Accuracy: ☐ <	oto, 🔛 ropograpine	i Map, Land Survey
3 LOCATE WELL	EPTH OF COMPLETED WI		c		
WITH AN "X" IN SECTION BOX:  N  WEI	th(s) Groundwater Encountered LL'S STATIC WATER LEVEI	(1)36 1.38.73ft.	ft. (2) below land surface r	ft. (measured on mo/da	3)ft. ay/yr. <b>10/30/12</b>
	Pump test data: Well w	ater was	ft. after	hours pump	oing gpm
W - NW - NE - E EST. YIELD gpm. Well water was ft. after hours pumping gpm. Bore Hole Diameter ft. after in. to ft., and ft., and ft.					
	LL WATER TO BE USED AS:				
□ Domestic □ Feedlot □ Oil field water supply □ Dewatering □ Other (Specify below) □ Irrigation □ Industrial □ Domestic-lawn & garden ☒ Monitoring well					
S If yes, mo/day/yr sample was submitted					
5 TYPE OF CASING USED: Steel N PVC Other					
CASING JOINTS:  Glued  Clamped  Welded  Threaded					
CASING JOINTS:  Glued  Clamped  Welded  Threaded  Casing diameter  ft., Diameter  in. to  in. to  ft., Diameter  ft., Diameter					
Casing height above land surface 2ft					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ Steel ☐ Stainless Steel ☐ Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut, Other (specify)  SCREEN-PERFORATED INTERVALS: From ft. to 55					
From ft to ft From ft to ft					
From					
From					
6 GROUT MATERIAL: Neat cement Cement grout M Bentonite K Other Comba 1-10.					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Contribution.  Grout Intervals: From 33 ft. to 3 ft., From 3 ft. to 5 ft. to 5 ft. to 5 ft. ft. to 5 ft. ft. ft. ft. ft. ft. ft. ft. ft.					
What is the nearest source of no	ossible Stamination:	(	<b>D</b>	110111	. 10. 00
Septic tank	☐ Lateral lines ☐ Pit privy	Livestock p	ens 🔲 Insecticide	storage	er (specify below)
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well					
	☐ Seepage pit ☐ Feedyard	Fertilizer st	orage 🗆 Oil well/ga	s well	
Direction from well <b>East</b>			rom well560		• • • • • • • • • • • • • • • • • • • •
	LITHOLOGIC LOG	FROM	TO LITHO. LO	OG (cont.) <u>or</u> PLU	GGING INTERVALS
0 2 Binson 2 18 Tansut 18 31 Tansan	ablasting sand, dr	4			
2 18 Tansut	ary to damp	<u> </u>			
18 31 Tansan	ysitt to sitty san	a time qu	unea		
	ty sard, red gravi				
33 45 HALAY	Bln oitty sand to:	sara			
fine"	coarse sand				
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
	The Whitehale services :=	TON TO	11 1	. 1	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 2 constructed, reconstructed, or plugged					
under my jurisdiction and was completed on (mo/day/year)					
					المالية
under the business name of BOULDON ON by (signature) Lambs BURLU					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
	copy to WATER WELL OWNER a				
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212					