	¥7 ¥¥/¥¥/€ €	Division of Water Resources App. No. MW-4DR								
WATER WELL RECORD	Form WWC-5	Section Number Township No. Range Number								
	Fraction SE 1/4 SE 1/4 SE 1/4	1/4 10 T 11 S R 25 ZE W								
Street/Rural Address of Well Location; it	unknown, distance & direction	Global Positioning System (GPS) information:								
from nearest town or intersection: If at o	wner's address, check here	Latitude: .39.1062 (in decimal degrees)								
Home Months of the second	•	Longitude: 94.6158 (in decimal degrees)								
		Elevation:								
2 WATER WELL OWNER: Advanta	- Matala Degrating Inc	Datum: WGS 84, NAD 83, NAD 27 Collection Method:								
	ge Metals Recycling Inc. h 2nd Street	GPS unit (Make/Model: Google Earth)								
	City, KS 66118	Digital Map/Photo, Topographic Map, Land Survey								
City, Builto, Zii Gode . Kansas	City, KS 00110	Est. Accuracy:								
3 LOCATE WELL	10.30'	Δ								
WITH AN "X" IN 4 DEPTH OF C	COMPLETED WELL 40.30'	ft (2) ft (3)								
SECTION BOX: Depth(s) Ground	water Encountered (1)	ft helow land surface measured on mo/day/yr.								
N WELL'S STATE	SECTION BOX: N Depth(s) Groundwater Encountered (1)									
POT VICID										
NW NE Dawn Hale Diem										
W E Bore Hole Diame	TO BE USED AS: Public	water supply Geothermal Injection well								
□ □ □ Domestic	☐ Feedlot ☐ Oil field	vater supply Dewatering Uther (Specify below)								
	- SW - SB - Irrigation Industrial Domestic-lawn & garden Monitoring well									
Was a chemical/	Was a chemical/bacteriological sample submitted to Department? Yes V No									
	day/yr sample was submitted									
1 mile Water well disin	fected? Yes V No									
5 TYPE OF CASING USED: Steel	PVC Dther									
CACINIC TOTATES. Cloud Clan	ned [7] Welded 1/7 Three	ided								
Casing diameter .2" in. to .23.30	J ft., Diameter	in. to								
Casing height above land surface	in., Weight	lbs./ft., Wall thickness or gauge NoSch. 40								
TYPE OF SCREEN OR PERFORATION Steel Stainless Steel	MATERIAL: V PVC	☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel	None used (open hole)									
SCREEN OR PERFORATION OPENING	S ARE:									
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)										
Louvered shutter Key punched	Wire wrapped Saw cu	Other (specify)								
SCREEN-PERFORATED INTERVALS:	From49.39 II. to49	1.30' ft., From ft. to ft. ft. ft. ft. ft. ft.								
CDANEL DACK DITEDITALS.	From 18.30' of to 40	0.30' ft., From ft. to ft.								
	Erom ft to	ft From tt. to It.								
6 CROUT MATERIAL: Neat ceme	ent Cement grout Be	ntonite Other Concrete ft. to 18.30' ft., From ft. to ft.								
Grout Intervals: From .0 ft. to	2.0 ft., From 2.0	ft. to 18.30' ft., From ft. to ft.								
What is the nearest source of possible control	amination:									
	nes Pit privy Livest									
Sewer lines Cesspool	Sewage lagoon Fuel st	orage Abandoned water well ter storage Oil well/gas well Non PCB Transformer								
Watertight sewer lines Seepage p		nce from well175'								
FROM TO LITHOLOG	and the second s									
See Boring Log										
OCC DOTTING EDG										
T CONTENT OF THE OWNER.	DIS CEDEURIO ATLONI. TILL.	water well was 🖊 constructed 🖂 reconstructed or 🗀 plugged								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\sqrt{\omega} \) constructed, \(\sqrt{\omega} \) reconstructed, or \(\sqrt{\omega} \) plugged under my jurisdiction and was completed on \(\text{mo/day/year} \) \(\frac{0.1/1.0/13}{0.1/1.0/13} \) and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 606 This Water Well Record was completed on (mo/day/year) 02/28/13										
Lunder the bysiness name of PSA Enviro	nmental	by (signature)								
INSTRUCTIONS: Use typestriter or hell point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies										
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at										
Telephone 785-296-5522. Send one copy to WA' http://www.kdheks.gov/waterwell/index.html.	IER WELL OWNER and retain one	tor your records. Include too or power of constitution more. That its at								
KSA 82a-1212		Check: White Copy, Blue Copy, Pink Copy								

SITE SKETCH:				PROJECT NAME: GALAMBA PROJECT NO.: 01-R584 PROBE NO.: MW4 DATE: 9-9-03 SHEET: 1 of 1 LOGGED BY: GFM DRILLED BY: JB SURFACE ELEVATION: TOTAL DEPTH: 40' FIELD SCREEN METHOD: PID DRILLING METHOD: HSA SAMPLING METHOD: SPLIT SPOON GRAVEL PACK: SEAL: GROUT: BENTONITE					
#	SA	MPLE			10 2 2				
O DEPTH, 1	RECOVERY	FIELD SCREEN RESULTS (ppm)	DESCRIPTION		UNIFIED SOIL CLASSIFICATION CONSTRUC				
5 -	0	0	CINDERS AND BRICK R	JBBLE DRY		TIE CONC			
	50	0	DEBRIS, CINDERS, RUBBER MATERIAL, BLACK, DRY			BENTONI	BENTON PVC CASING	ø PVC CASING BENTONIT	
10 - - 15	10	0	DEBRIS AND CINDERS, BLACK SA BLACK CLAY. DRY, BLACK, ORGA R.R. TIES)			2"8 P			
20 -	20	0	DEBRIS AND TRASH. BLACK 15'-16' SATURATED. 16'-20' DAMP			- -			
25 -	20	0	20'-21' SATURATED CLAYEY SILT. 21'-25' BLACK CLAYEY SILT, DAMP. SAND LENSES AT 24'			- - - -			
30 -	10	0	BLACK AND GRAY CLAY, DAMP, VI SILT LENSES			-	SILICA SAND SLOT PVC SCREEN SLOT PVC SCREEN		
35 -	10	0	BLACK AND GRAY CLAY, DAMP, VERY STIFF. SAND AND SILT LENSES THEN SATURATED FINE TAN SAND				SILICA 0.010 SLOT P		
40 -	10 0		SATURATED FINE TA	SATURATED FINE TAN SAND					
-			40' B.O.B.				40' BO OF SCI		
45 -		i Sariy							
50 -	- · · · ·								

THE SIRVEY