

County: Wyandotte Fraction NE NE SE SE Sec. 10 T 11 S R 25 (E)W

CORRECTION(S) TO WATER WELL COMPLETION RECORD (WWC-5)

(to rectify lacking or incorrect information)

Owner: Advantage Metals Recycling Inc.

Location was listed as:

Location changed to:

Section-Township-Range: 10-11S-25E

10-11S-25E

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): None Given

NE NE SE SE

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

Verification method: Latitude & Longitude, KGS' "LEO" conversion tool,
and mapping tool on KGS website, Google Earth.

initials: DR date: 6/20/2013

Submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726

to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

MW-5S

Check: ☐ White Copy, ☐ Blue Copy, ☐ Pink Copy

SITE SKETCH:

MONITORING WELL LOG

PROJECT NAME: GALAMBA

PROJECT NO.: 01-R584

PROBE NO.: MW5

DATE: 9-10-03

SHEET: 1 of 1

LOGGED BY: GFM

DRILLED BY: JB

SURFACE ELEVATION:

TOTAL DEPTH: 40'

FIELD SCREEN METHOD: PID

DRILLING METHOD: HSA

SAMPLING METHOD: SPLIT SPOON

GRAVEL PACK:

GROUT: BENTONITE

DEPTH, ft.	SAMPLE		DESCRIPTION	UNIFIED SOIL CLASSIFICATION	WELL CONSTRUCTION	
	RECOVERY	FIELD SCREEN RESULTS (ppm)				
0			CONCRETE		CONCRETE	
70	0		CLAY AND DEBRIS FILL MATERIAL. DRY FINE, TAN SAND FILL, DRY			
5						
60	0		FINE TAN SAND AND SILTY SAND DAMP			
10						
60	0		WET, LIGHT BROWN, SILTY SAND		BENTONITE	2" PVC CASING
15						
10	0		GRAY, CLAYEY SILTY, SATURATED COARSE TAN SAND AT 20' SATURATED			
20						
30	0		COARSE, TAN, DRY SAND		SAND	
25						
20	0		FINE, TAN, DAMP SAND			
30						
10	0		FIN TAN SAND, MOIST. BECOMES SATURATED AT ABOUT 31.5'			0.010' SLOT PVC SCREEN
35						
0	0		FINE TAN SATURATED SAND			
40						
			40' B.O.B.			40' BOTTOM OF SCREEN
45						
50						

