				TER WELL RE	CORD For	m WWC-5	KSA 828	1-1212 IE) No			
_	ON OF WATE		Fraction	_		Sec	tion Numbe	er To	wnship Number	Rar	nge Numb	er
	Wyar		SW 1/2			1/4	15	Т	11 s	R	25	Е
201 S. 5 ^{tt}	' – Kansas	City	_	address of well	if located wi	thin city?						
2 WATER	WELL OWNE	R: Union I	Pacific Rai	Iroad								
RR#, St. Add	dress, Box#	: 1400 D	ouglas St.					Boar	rd of Agriculture,	Division of W	Vater Reso	urces
City, State, 2	ZIP Code	: Omaha	, NE 6817	9					ication Number:			
LOCATE	WELL'S LOC	ATON WITH	4					•				
AN "X" IN	N SECTION BO	<u> </u>		COMPLETED		45	ft. ELI	EVATION:	7	56.49 (TC)C)	
†			Depth(s) Grou	ndwater Encou	untered 1	36	.5	ft. 2	fi	. 3		ft.
	NW	NE	WELL'S STAT	IC WATER LE	VEL	ft.	below land	i surface m	easured on mo/o	lay/yr		
	i	i	Pur	mp test data:	Well water	was		ft. after	hou	rs pumping		gpm
∮ ₩ -	X	┊	Est. Yield	gpm:	Well water	was		ft. after	hou	rs pumping		gpm
ī			Bore Hole Dia	meter 8	in. to	4	5	ft. and		in. to		ft.
 -	-sw	· SE	WELL WATER	R TO BE USED	AS: 5 Pu	blic water s	upply	. 8 Ai	r conditioning ewatering	11 Injectio	on well	
	i 1	i	1 Domes	stic 3 Feed k	ot 6 Oil	field water	supply	9 D	ewatering	12 Other	(Specify be	elow)
٧ <u>L</u>	s		2 Irrigatio	on 4 Industr	rial 7 La	wn and gard	den (domes	stic) 10 l	Monitoring well	<u> </u>		
	3								No X If			
		1	submitted	_	•				Disinfected? Yes		-	
5 TYPE OF	BLANK CAS			5 Wmin	tht Iron				SING JOINTS: G			1
1 Ste			SR)	•	tos-Cement					/elded	_ 0.2pcc	"
2 PV		74 ABS	,,,,			3 Outer	(specify be	10 10)			Eluck	
				7 Fibergi						readed		1
	diameter			50	ia	in. t	to	ft., Dia	ı	in. to		ft.
Casing heigi	ht above land	surface	0	in., weight	0	.703	ibs./f	t. Wall thic	kness or gauge l	No	SCH. 40)
	CREEN OR PI		MATERIAL:				PVC		10 Asbestos-ce	ment		
1 Ste	el	3 Stainles	ss steel	5 Fiberg	lass	8	RMP (SR)		11 Other (spec	ify)		
2 Bras		4 Galvan		6 Concre	ete tile	9	ABS		12 None used			
SCREEN OF	R PERFORAT				5 Gauze	d wrapped				11 Non	e (open h	ole)
1 Cor	ntinuous slot	3 1	Mill slot		6 Wirew	rapped		9 Dril	led holes			
2 Lou	wered shutter	4 1	Key punched		7 Torch	zut		10 Ott	ner (specify)			
SCREEN-PE	ERFORATED	INTERVALS:	From	30	ft. to	45	ft.	From		ft. to		fi
								From		ft to		·#
GRA	AVEL PACK IN	ITERVALS:	From	27	ft. to	45	۳ ه	Emm		# to		'L
0.0		TERRITO.	From									
6 00015	MATERIAL	4 11. 4			il to					ft. to		ft.
				2 Cement gro			tonite					
Grout Interva	als From _.	<u> </u>	t. to 27	ft. From	n	ft. t	io	ft.	From	fl. to		ft.
	nearest source	of possible o	ontamination:					estock pen:	s 14	Abandoned	water well	l
•	otic tank		4 Lateral line	s 7	7 Pit privy			l storage	· -	Oil well/ Gas	s well	
	ver lines		5 Cess pool	1	8 Sewage la	agoon	12 Feri	tilizer stora	ge 16	Other (speci	ify below)	
Ì	tertight sewer l	ines	Seepage pi	it !	9 Feedyard		13 Inse	ecticide sto	rage			
Direction from							How mar	ny feet?				
FROM	TO	CODE		OLOGIC LOG		FROM	ТО		PLUGGING	3 INTERVAL	.s	
0	5		recovery									
_	7 .		, black sand,	gravelly, and	d dark gray							
5 7.5	7.5 22.5	silt	L	-le be			 	 				
7.5	22.3		, brown to pa				 	 				
22.5	28			to fine grains some fine gr		1	1	1				
	20			grained, pale			+	 -				
28	32.5		ici, medium (le coarse san	• .	DIOWII,		1					
	72.7			edium graine	ed nale	 	+	+				
32.5	40	brov	•	Alank	a, paio		1	Survey	date: 10/07/1	3. NAD R	3 KS SP	С
				parse grained	i. brown.	-	 		IVIVII	J, 0		
40	42.5			clay layer at			1	North:	295601.1 ft			
42.5			ology not		- 1-11		 		2271081.2 ft			
	CTOR'S OR I				ater well was	(1) construc	ted (2) red		i, or (3) plugged u		ediction an	d was
				02/13								
	n (mo/day/yr)			531					best of my know	-		
	Contractor's Lie							7/	s completed on (i	no/day/yr)	10/23	/13
	ISTICALS: Place			gineering,		by	(signature) //n	1 //2	D	later 1995	0141
									h and Environment nd retain one for y		vatter, 1000	2 M
200.001	,, , ,			J.Spilono. 010-		0110 (0 74/	· · - · · · · · · · · · · · · · · · · ·		in rotain the for y	our records.		