County: Wyandotte Fraction SE SE SW SE Sec. 15 T // S R 23 (E/W)
CORRECTION(S) TO WATER WELL COMPLETION RECORD (WWC-5)
(to rectify lacking or incorrect information)
Owner: Kansas Avenue Properties
/ Location changed to:
Location was listed as:
Section-Township-Range: $1/5-25E$ $3-1/3-25E$
Section-Township-Range: $//5-25E$ $/5-1/5-25E$ Fraction ($1/4$ $1/4$): $/4$ $1/4$
Other changes: Initial statements:
Changed to:
Comments:
Verification method: Latitude & Longitude, KGS' LEO" conversion tool, wellsite address & city street map, and mapping tool & aerial photos on KGS website initials: [Predate: 1//14/20/3]
usellsite address & city street map, and mapping tool &
initials: Ordate: 11/14/20/3
Submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726/
Submitted by: Kansas Geological Survey, Data Resources Distary, 1995 Committed by: Kansas Geological Survey, Data Resources Distary, 1995 Committed by: Kansas Geological Survey, Data Resources Distary, 1995 Committed by: Kansas Geological Survey, Data Resources Distary, 1995 Committed by: Kansas Geological Survey, Data Resources Distary, 1995 Committed by: Kansas Geological Survey, Data Resources Distary, 1995 Committed by: Kansas Geological Survey, Data Resources Distary, 1995 Committed by: Kansas Geological Survey, Data Resources Distary, 1995 Committed by: Kansas Geological Survey, Data Resources Distary, 1995 Committed by: Resou

I LOCATION OF WITER WELL: Fraction
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here
Latitude: 37.57. C.3
Continuous Con
Ref. Strott Address Box # 24 Depth (s) Groundwater Encountered Costing Notes Cost
WATER WELL OWNER:
RR#, Street Address, Box #: 3440 134th Parable Golgetion Mide/Model: 5443 Golgetion Midel Model: 5443 Golgetion Midel Model: 5443 Golgetion Midel Model: 5443 Golgetion Midel Model: 5443 Golgetion Model: 5443 Golgetion Midel Model: 5443 Golgetion Midel Model: 5443 Golgetion Midel: 5443 Golgetion Model: 5443 Golgetion Midel: 5443 Golgetion Model: 5443 Golgetion Midel: 5443 Golgetion Model: 5443 Golgetion Model
3 LOCATE WELL WITH AN "X" IN SECTION BOX: N 4 DEPTH OF COMPLETED WELL SECTION BOX: N Depth(s) Groundwater Encountered WELL S STATIC WATER LEVEL S. Pump test data: Well water was. ft. after. hours pumping. gpm Bore Hole Diameter SET, YIELD. gpm, Well water was. ft. after. hours pumping. gpm Bore Hole Diameter SET, YIELD Domestic Feedlot Diffield water supply Dewatering Other (Specify below)
S LOCATE WELL WITH AN "X" IN SECTION BOX: N
WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft.
Pump test data: Well water was
Pump test data: Well water was
STYPE OF CASING USED: Steel PVC Other Other (Sasing height above land surface. Melbar Me
NW
Domestic Feedlot Oil field water supply Geothermal Injection well
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)
Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No
S
Water well disinfected? Yes No S TYPE OF CASING USED: Steel PVC Other
S TYPE OF CASING USED: Steel PVC Other
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to in. in. to in. to in. to in. in. to in. to in. in. in. in. in. in. in. in. in.
Casing height above land surface. Flucks: Man., Weight lbs./ft., Wall thickness or gauge No. Sch. Vo. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From S. ft. to D. ft., From ft. to ft. GRAVEL PACK INTERVALS: From S. ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. GROUT MATERIAL: Neat cement Cement grout Bentonite Other (specify below) What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) SCREEN-PERFORATED INTERVALS: From S5 ft. to P ft., From ft. to ft. GRAVEL PACK INTERVALS: From S5 ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft. Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)
Steel Stainless Steel PVC Other (Specify)
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From. 35. ft. to 20. ft., From ft. to ft. From. ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From. 35. ft. to 18. ft., From ft. to ft. From. ft. to ft., From ft. to ft. From. ft. to ft., From ft. to ft. GROUT MATERIAL: Neat cement Cement Grout Bentonite Other Constitution Grout Intervals: From ft. to ft. Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 3.5 ft. to 2.0 ft., From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 3.5 ft. to 1.8 ft., From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. GROUT MATERIAL: Neat cement Cement Grout Bentonite Other Contains Grout Intervals: From ft. to ft., From ft. to ft. Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)
SCREEN-PERFORATED INTERVALS: From. 35 ft. to 20 ft., From ft. to ft. GRAVEL PACK INTERVALS: From. 35 ft. to 18 ft., From ft. to ft. From. ft. to ft., From ft. to ft. From. ft. to ft., From ft. to ft. From. ft. to ft. Septic tank
GRAVEL PACK INTERVALS: From 35 ft. to 18 ft., From ft. to ft. From ft. to ft., From ft. to ft. GROUT MATERIAL: Neat cement Cement grout Bentonite Other ft. ft. of ft. Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)
Grout Intervals: From
Grout Intervals: From
Grout Intervals: From
What is the nearest source of possible contamination: Septic tank Livestock pens Insecticide storage Other (specify below)
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)
Westersials and the second sec
Direction from well . East
FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 2.0 Rail ron 1. Ballan
20 7.0 Black Vayersitt
1.D 16.D BLACK - DK RIAU pittly para
12 D 27 D HI All - Bl A All - 20 All
27.0 30.0 High Line Coalse pand
30.0 32.0 Bigg day, with
32.D 35.DELACIFINE-LOQUE. MANA
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION. THE
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, or plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.
ixalisas water well conflacture Science No This water well Record was completed on (moldowless)
under the business and the basis of the basi
INCERTIFICATIONS AND SIGNATURE DE SIGNATURE
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at