MW-15

WATER WELL RECORD	Form WW	VC-5		r Resources App. N		
1 LOCATION OF WATER WELL: County: WUAN Joff e	Fraction NE 14 NE 14	1/4 1/4	1		Range Number R 25 ØE □W	
Street/Rural Address of Well Location;	if unknown, distance &	direction	Global Positioning	System (GPS) in	nformation:	
from nearest town or intersection: If at owner's address, check here [A]. Latitude: 2.7.796516.19. Longitude: 2.7.2566.19. Lon					(in decimal degrees) (in decimal degrees)	
	Elevation:?	47.66	 1 NAD 22			
2 WATER WELL OWNER: PRI/fordon FACILITY			Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: 3 co < 3 co < 5 co			GPS unit (Make/Model: I Phone			
City, State, ZIP Code : 388 3. 324 37. 66215			Digital Map/Photo, Topographic Map, Land Survey Est. Accuracy: St. Accuracy : <a< td=""></a<>			
WITH AN "X" IN 4 DEPTH OF	WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1)					
N WELL'S STATIC WATER LEVEL 4-0 ft below land surface measured on molday/yr						
Pump test data: Well water was						
Pump test data: Well water was A.A. ft. after hours pumping gpm EST. YIELD A.A. gpm, Well water was ft. after hours pumping gpm Bore Hole Diameter in. to 3.5 ft., and in. to ft.						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
S If yes, mo/day/yr sample was submitted						
Water well disinfected? ☐ Yes 🖟 No						
5 TYPE OF CASING USED: Steel N PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in to 2						
Casing diameter						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut SCREEN-PERFORATED INTERVALS: From £5 ft. to \$5 ft., From ft. to ft.						
SCREEN-PERFORATED INTERVALS: From 25 ft. ft. From ft. to ft.						
From						
GRAVELTACK HYTERVALD.	From ft.	to	ft., From		to It.	
From ft. to ft., From ft. to ft. 6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Report of to ft. Grout Intervals: From C. ft. to 20 ft., From ft. to ft.						
What is the nearest source of possible contamination:						
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well						
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well K5 Livel						
Direction from well N.E.		Distance i		Feet		
FROM TO LITHOLOGO	20cK	FROM	TO LITHO. LO	G (cont.) <u>or</u> PLU	GGING INTERVALS	
To Temental Of						
10 20 Clay with Sm	d-BILin color					
20 35 SAND/ little C/A	4					
7 CONTRACTOR'S OR LANDOWNER	'S CEPTIFICATION.	This water	well was 57 seeds	atad Danner	-4-1 []-1	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 2 14/1/4 and this record is true to the loss of my knowledge and belief.						
Kansas Water Well Contractor's License No. 793 This Water Well Record was completed on molecularly year was 15.15. under the business name of Canaly Pump Stands by (signature)						
under the business name of LALLACLAT.			by (signature)			
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and pleck the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at						