WATER WELL RE		Form V	WWC-5	Di	vision of Water			
Original Record			e in Well Use		sources App. No		Well ID	
1 LOCATION OF WATER WELL:			Fraction					
County: Wyandotte	1/4 SE 1/4 NW 1/							
2 WELL OWNER: Last Name: First:				Street or Rural Address where well is located (if unknown, distance and				
Business: Phillips 66 Address: 1604-02 Ph		direction from nearest town or intersection): If at owner's address, check here:						
Address: 1004-02 PT		1800 N. 10	th St., Kansa	s City, MO				
City: Bartlesville	ZIP: 74003							
3 LOCATE WELL 4 DEPTH OF COMPLETED WELL:34,0 ft. 5 Latitude: 39, 12366 (decim								
WITH "X" IN			Encountered: 1)		Longit	de 94.635	.7(decimal degree	
SECTION BOX:			3) ft., or 4)	☐ Dry Well Horizontal Datum: ■ WGS 84 ☐ NAD 83 ☐ NAD 27				
	WELL'S STATIC WATER LEVEL:					for Latitude/Longitude	:	
	, measured on (mo-day			GPS (unit make/model:Garmin 60c) (WAAS enabled? ■ Yes □ No)				
NW NE	, measured on (mo-day							
w + w + w = w	vater wass pumping							
	Well water was							
SW SE	after	hours	s pumping	gpm	(F)	6 Elevation:		
	Estimated Yi	eld:	gpm 10.25 in. to 34.0					
S	Bore Hole Di				Source:			
1 mile Other ft.								
7 WELL WATER TO			iter Supply: wall ID		10 🗖 🖓	Field Water Supply: 1	eace	
Household	= ***							
☐ Lawn & Garden	echarge: well ID			☐ Cased ☐ Uncased ☐ Geotechnical				
☐ Livestock								
2. Irrigation								
3. Feedlot Air Sparge								
	4. Industrial Recovery Injection 13. Other (specify):							
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ■ No If yes, date sample was submitted:								
Water well disinfected? ☐ Yes ■ No								
8 TYPE OF CASING USED: ☐ Steel ☐ PVC ☐ Other								
Casing diameter 4.0 in to 14.0 ft., Diameter in to ft., Diameter in to ft., Diameter in to ft. Casing height above land surface -0.2 in Weight surface lbs/ft. Wall thickness or gauge No. Sch. 40								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous Slot								
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole) SCREEN-PERFORATED INTERVALS: From .34.0 ft. to .14.0 ft., From .7 ft. to .7 ft. to .7 ft. to .7 ft.								
GRAVEL PACK INTERVALS: From34.0. ft. to12.0. ft., From ft. to ft., From ft. to ft. o ft.								
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From 12.0 ft. to 2.0 ft., From ft. to ft., From ft. to ft.								
Nearest source of possible contamination:								
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage								
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well								
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well								
☐ Other (Specify) Direction from well? Distance from well? ft.								
10 FROM TO			GIC LOG	FROM			r PLUGGING INTERVAL	
	ilty Clay w/F							
	ilty Clay							
				1	1L			
	Notes:							
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo-day-year) .8/4/20.15								
Kansas Water Well Cont	ractor's Lice	nse No	7.10 This W	ater Well Re	cord was com	pleted on (mo-day-y	ear) .8/1.1/201.5	
under the business name	of Below C	iround S	urtace, Inc		M			
Mail I white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.								
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 1/20/2015								