

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number																																	
County: Wyandotte		1/4 NW 1/4 NW 1/4		21		T 11 S		R 25 EW																																	
Distance and direction from nearest town or city street address of well if located within city? 1806 Kansas Ave. KC, KS 66105 MW 14																																									
2 WATER WELL OWNER: Colgate Palmolive Co. RR#, St. Address, Box #: 1806 Kansas Ave. City, State, ZIP Code: Kc, KS 66105 Board of Agriculture, Division of Water Resources Application Number:																																									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 45.5 ft. ELEVATION:																																							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.25 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No																																							
		5 TYPE OF BLANK CASING USED:																																							
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 2 in. to 25 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface -2 in., weight lbs./ft. Wall thickness or gauge No. Sch 40																																							
		TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)																																							
SCREEN-PERFORATED INTERVALS: From 45' ft. to 25' ft. From ft. to ft.																																									
GRAVEL PACK INTERVALS: From 23' ft. to 45' ft. From ft. to ft.																																									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete																																									
Grout Intervals: From 2 ft. to 23 ft. From ft. to ft. From 0 ft. to 2 ft.																																									
What is the nearest source of possible contamination:																																									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?																																									
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>4'</td> <td rowspan="5">F. 11 silty gravel brick Clayey silt with sandy zones F. into medium silty sand Clayey silt with sand layers silty fine sand</td> <td></td> <td></td> <td></td> </tr> <tr> <td>4'</td> <td>21'</td> <td></td> <td></td> <td></td> </tr> <tr> <td>21'</td> <td>22'</td> <td></td> <td></td> <td></td> </tr> <tr> <td>22'</td> <td>33'</td> <td></td> <td></td> <td></td> </tr> <tr> <td>33'</td> <td>45.5'</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	4'	F. 11 silty gravel brick Clayey silt with sandy zones F. into medium silty sand Clayey silt with sand layers silty fine sand				4'	21'				21'	22'				22'	33'				33'	45.5'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																				
0	4'	F. 11 silty gravel brick Clayey silt with sandy zones F. into medium silty sand Clayey silt with sand layers silty fine sand																																							
4'	21'																																								
21'	22'																																								
22'	33'																																								
33'	45.5'																																								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 2/27/98 under the business name of Terracon Inc. by (signature) Ronald G. Gallette																																									