

1 LOCATION OF WATER WELL: County: Wyandotte		Fraction $\frac{1}{4}$ NW $\frac{1}{4}$ NW $\frac{1}{4}$		Section Number 21	Township Number T 11 S	Range Number R 25 EW	
Distance and direction from nearest town or city street address of well if located within city? 1806 Kansas Ave. KC, KS 66105 MW 19							
2 WATER WELL OWNER: Colgate Palmolive Co. RR#, St. Address, Box # : 1806 Kansas Ave. City, State, ZIP Code : KC, KS 66105				Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 455 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter. . . 8.25 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No					
		5 TYPE OF BLANK CASING USED:					
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped ☒ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. X Blank casing diameter 2 in. to 25 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface. 2 in., weight lbs./ft. Wall thickness or gauge No. . . Sch. 40					
		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel ☒ Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ☒ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From . . . 25 ft. to . . . 45 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From . . . 23 ft. to . . . 45 ft., From ft. to ft. From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ Bentonite 4 Other Concrete							
Grout Intervals: From . . . 2 ft. to . . . 23 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?							
FROM		TO		LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS	
0		5		Fill, Gravel, Brck, silt			
5		21		Clayey silt			
21		28		Sandy silt			
28		45.5		Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. . . . 416 This Water Well Record was completed on (mo/day/yr) . . . 2/23/98 under the business name of Terracon Inc. by (signature) <i>Ronald G. Glatte</i>							