

MW3

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Wyandotte		SW 1/4 SW 1/4 SW 1/4	15	T 11 S	R 25 E
Distance and direction from nearest town or city street address of well if located within city? 970 Scott, Kansas City, KS.					
2 WATER WELL OWNER: Praxair					
RR#, St. Address, Box # : 2301 SE Creekview Dr.			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Ankan, IA. 50021			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 33 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 28 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 24.40 ft. below land surface measured on mo/day/yr 12-15-97			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8.5 in. to 33 ft. and in. to ft.			
WELL WATER TO BE USED AS:					
1 Domestic      3 Feedlot      6 Oil field water supply      8 Air conditioning      11 Injection well 2 Irrigation      4 Industrial      7 Lawn and garden only      9 Dewatering      12 Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel      3 RMP (SR)      5 Wrought iron      8 Concrete tile      CASING JOINTS: Glued      Clamped 2 PVC      4 ABS      6 Asbestos-Cement      9 Other (specify below)      Welded Blank casing diameter 2.375 in. to 18 ft. Dia. in. to SDR 13 ft. Casing height above land surface FLUSH MT. in., weight lbs./ft. Wall thickness or gauge No. SCh. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel      3 Stainless steel      5 Fiberglass      8 RMP (SR)      10 Asbestos-cement 2 Brass      4 Galvanized steel      6 Concrete tile      9 ABS      11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE:      5 Gauzed wrapped      8 Saw cut      11 None (open hole) 1 Continuous slot      3 Mill slot      6 Wire wrapped      9 Drilled holes 2 Louvered shutter      4 Key punched      7 Torch cut      10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From ft. to 18 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 33 ft. to 16 ft. From ft. to ft.					
6 GROUT MATERIAL:					
Grout Intervals: From 16 ft. to 3 ft. From 4 ft. to 0 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank      4 Lateral lines      7 Pit privy      10 Livestock pens      14 Abandoned water well 2 Sewer lines      5 Cess pool      8 Sewage lagoon      11 Fuel storage      15 Oil well/Gas well 3 Watertight sewer lines      6 Seepage pit      9 Feedyard      12 Fertilizer storage      16 Other (specify below)					
Direction from well? SE How many feet? 100					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	.50	Concrete			
.50	25	Brn silt, soft, moist, friable.			
25	33	Clayey silt, sand at 28', well sorted, med-coarse grains, sub angular, no odor.			
FL. mt. OK'D by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-3-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 2-13-98 under the business name of JB Environmental Drilling by (signature) James Buebel					