

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: WYANDOTTE		SE ¼ SE ¼ SE ¼	17	T 11 S	R 25 EW
Distance and direction from nearest town or city street address of well if located within city? 1814 KANSAS AVE., KANSAS CITY, KS					
2 WATER WELL OWNER:		AMERICAN INGREDIENTS CO.		MW-2	
RR#, St. Address, Box # :		3947 BROADWAY		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code :		KANSAS CITY, MO 64111		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 28 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 28.70 ft. below land surface measured on mo/day/yr 07-06-98			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 1/4 in. to 40 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No ☒			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
☒ PVC		4 ABS		6 Asbestos-Cement	
Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft.		7 Fiberglass		9 Other (specify below)	
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. SCHED. 40				CASING JOINTS: Glued Clamped Welded Threaded ☒	
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		8 RMP (SR)	
				9 ABS	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		☒ Mill slot		5 Gauzed wrapped	
2 Louvered shutter		4 Key punched		6 Wire wrapped	
				7 Torch cut	
				8 Saw cut	
				9 Drilled holes	
				10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 40 ft. to 30 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 40 ft. to 28 ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		☒ Bentonite	
Grout Intervals: From 28 ft. to 1 ft., From ft. to ft., From ft. to ft.				4 Other	
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well? How many feet?					
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
0		5		Brn Clay	
5		30		Brn Silty Clay	
30		40		Brn Sand	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-29-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 568 This Water Well Record was completed on (mo/day/yr) 7-2-98 under the business name of NASE by (signature) David Hunch					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					