

LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Wyandotte		SE ¼ NE ¼ NW ¼	2	T 11 S	R 25 E/W
Distance and direction from nearest town or city street address of well if located within city? Kansas City, Kansas					
WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Phillips Petroleum Company Bartlesville, Oklahoma 74004 Board of Agriculture, Division of Water Resources Application Number:			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 20.0 ft. ELEVATION: @ 12.0 ft.			
		Depth(s) Groundwater Encountered 1. ... ft. 2. ... ft. 3. ... ft. WELL'S STATIC WATER LEVEL ... ft. below land surface measured on mo/day/yr Pump test data: Well water was ... ft. after ... hours pumping ... gpm Est. Yield ... gpm; Well water was ... ft. after ... hours pumping ... gpm Bore Hole Diameter .5 in. to 20.0 ft., and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped Welded Threaded X			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)					
Blank casing diameter 2 in. to 5.0 ft., Dia ... in. to ... ft., Dia ... in. to ... ft. Casing height above land surface 2.4 in., weight ... lbs./ft. Wall thickness or gauge No sch-40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) ... 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ...			
SCREEN-PERFORATED INTERVALS: From 5.0 ft. to 20.0 ft., From ... ft. to ... ft. GRAVEL PACK INTERVALS: From 5.0 ft. to 20.0 ft., From ... ft. to ... ft.					
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0.45 ft. to 5.0 ft., From 0.10 ft. to 4.5 ft., From ... ft. to ... ft.					
What is the nearest source of possible contamination?		refinery tanks			
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? 50' and lines					
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG					
0 12.0 grey sandy silty clay - wet soft 03 12.0 20.0 grey sand - wet - 05					
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed/reconstructed/plugged under my jurisdiction and was completed on (mo/day/year) 2-1-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 438 This Water Well Record was completed on (mo/day/yr) 2-1-83 under the business name of Kansas City Testing Lab by signature Jim Rodgers					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					