


WELL # 75

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: WYANDOTTE		Fraction NE 1/4 NW 1/4 NE NW 1/4	Section Number 2	Township Number T 11 S	Range Number R 25 E
Distance and direction from nearest town or city street address of well if located within city? KANSAS CITY, KS.					
2 WATER WELL OWNER: PHILLIPS PETROLEUM CO, BARTLESVILLE, OKLAHOMA 74004 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 25.0 ft. ELEVATION: 18.0 ft. Depth(s) Groundwater Encountered 1. 18.0 ft. 2. 18.0 ft. 3. 18.0 ft. WELL'S STATIC WATER LEVEL 18.0 ft. below land surface measured on mo/day/yr Pump test data: Well water was 18.0 ft. after 18.0 hours pumping 18.0 gpm Est. Yield 18.0 gpm: Well water was 18.0 ft. after 18.0 hours pumping 18.0 gpm Bore Hole Diameter 5 in. to 25.0 ft., and 25.0 in. to 25.0 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Blank casing diameter 2 in. to 5.0 ft., Dia. 5.0 in. to 5.0 ft., Dia. 5.0 in. to 5.0 ft. Casing height above land surface 2.4 in., weight 2.4 lbs./ft. Wall thickness or gauge No. 2.4 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 4 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 5.0 ft. to 25.0 ft., From 5.0 ft. to 25.0 ft., From 5.0 ft. to 25.0 ft. GRAVEL PACK INTERVALS: From 5.0 ft. to 25.0 ft., From 5.0 ft. to 25.0 ft., From 5.0 ft. to 25.0 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4.5 ft. to 5.0 ft., From 5.0 ft. to 5.0 ft., From 5.0 ft. to 5.0 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? 50' REFINERY TANKS How many feet? 50' FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG 0 12.0 GREY SILTY SAND, MOIST 12.0 25.0 GREY SAND					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-27-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 438 This Water Well Record was completed on (mo/day/yr) 1-31-83 under the business name of KANSAS CITY TESTING LABORATORY by (signature) Jim R. R. R. INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					