

1 LOCATION OF WATER WELL: County: Wyandotte NE 1/4 NE 1/4 NE 1/4 Section Number 3 Township Number 11 S Range Number 25 EW

Distance and direction from nearest town or city street address of well if located within city? 600 feet & 60° azimuth bearing from 1st & Walker K.C., Ks.

2 WATER WELL OWNER: Dancy Corporation RR#, St. Address, Box #: 1st & Walker City, State, ZIP Code: K.C., Ks

Board of Agriculture, Division of Water Resources Application Number: 721.5

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in NE corner]

4 DEPTH OF COMPLETED WELL: 28.0 ft. ELEVATION: 721.5 ft.

Depth(s) Groundwater Encountered 1. 16.0 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 3.35 5.24 Below land surface measured on mo/day/yr 7/24/89

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 in. to 28.0 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter 2 in. to 8.0 ft., Dia 0.93 in. to ft., Dia 0.254 in. to ft.

Casing height above land surface 2.0 in., weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut

SCREEN-PERFORATED INTERVALS: From 8.0 ft. to 22.5 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 6.0 ft. to 28.0 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 8.0 ft. to 4.0 ft., From 4.0 ft. to 6.0 ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) former refinery site

Direction from well? well drilled on former refinery site

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0 4.5 general fill

4.5 16 silty clay - low plasticity

16 23.5 silty clay - highly plastic

23.5 28 clayey silt

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/17/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 399 This Water Well Record was completed on (mo/day/yr) 10-17-89 under the business name of WARDWARD-CITY CONSULTANTS by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.