

1 LOCATION OF WATER WELL: County: WYANDOTTE		Fraction NW 1/4 NW 1/4 NW 1/4	Section Number 7	Township Number T 11 S	Range Number R 25 EW
Distance and direction from nearest town or city street address of well if located within city? MONTGOMERY WARDS AUTO CENTER, INDIAN SPRINGS SHOPPING CENTER					
2 WATER WELL OWNER: K. S. CENTER LP RR#, St. Address, Box #: 4601 STATE AV City, State, ZIP Code: KANSAS CITY, KS 66102			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 19.90 ft. ELEVATION: GROUND SURFACE			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 19.80 ft. below land surface measured on mo/day/yr 6-21-92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 in. to 20 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ☒			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded ASTM-F480 Blank casing diameter in. to 5 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface: 1 in., weight lbs./ft. Wall thickness or gauge No. SC.H. 40			
		TYPE OF SCREEN OR PERFORATION MATERIAL:			
SCREEN OR PERFORATION OPENINGS ARE:		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot ☒ Mill slot 0.010 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 5 ft. to 20 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 3 ft. to 20 ft., From ft. to ft. From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement ☒ Cement grout ☒ Bentonite 4 Other					
Grout Intervals: (2) From 0 ft. to 1 ft. (3) From 1 ft. to 3 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage ☒ Other (specify below) EXCAVATED TANK PIT Direction from well? W How many feet? 5'					
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
0		0.6		CONCRETE	
0.6		2		SAND BASE	
2		11		LT. RD BRN, MOTTLED SILTY CLAY	
11		11.1		LIMESTONE (FRACTURED)	
11.1		13		BR SANDY WEATHERED SHALE	
13		13.5		LIMESTONE (WEATHERED)	
13.5		20		BR to GRAY SHALE w THIN LIMESTONE PARTINGS	
20				LIMESTONE REFUSAL	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-18-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 530 This Water Well Record was completed on (mo/day/yr) 6-30-92 under the business name of SHAMROCK ENVIRONMENTAL DRILLING INC. by (signature) Clay G. Allyn					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answer. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC

1/4

1/4

1/4