


1 LOCATION OF WATER WELL: County: WYANDOTTE		Fraction: SW 1/4 NE 1/4 SE 1/4	Section Number: 14	Township Number: T 11 S	Range Number: R 25 E																																										
Distance and direction from nearest town or city street address of well if located within city? 1600 Genesee, Kansas City, MO																																															
2 WATER WELL OWNER: N.F. Building Corporation RR#, St. Address, Box #: 4800 Main City, State, ZIP Code: Kansas City, MO 64112 Board of Agriculture, Division of Water Resources Application Number: 960760																																															
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 38.5 ft. ELEVATION: 760 Depth(s) Groundwater Encountered: 1 30.0 ft. 2 33.0 ft. 3 ft. WELL'S STATIC WATER LEVEL: 25.25 ft. below land surface measured on mo/day/yr: 5/23/91 NA Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm Bore Hole Diameter: 7.0 in. to 45.0 ft., and _____ in. to _____ ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes _____ No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted _____ Water Well Disinfected? Yes _____ No <input checked="" type="checkbox"/>																																													
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued _____ Clamped _____ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded _____ Blank casing diameter: 2.0 in. to 38.5 ft., Dia _____ in. to _____ ft., Dia _____ in. to _____ ft. Casing height above land surface: Flush mount in., weight 1.0 lbs./ft. Wall thickness or gauge No. Sch 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) _____ 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) _____ SCREEN-PERFORATED INTERVALS: From 28.0 ft. to 38.0 ft., From _____ ft. to _____ ft. From _____ ft. to _____ ft., From _____ ft. to _____ ft. GRAVEL PACK INTERVALS: From 25.0 ft. to 45.0 ft., From _____ ft. to _____ ft. From _____ ft. to _____ ft., From _____ ft. to _____ ft.																																															
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other _____ Grout Intervals: From Surface ft. to 23.0 ft., From 23.0 ft. to 25.0 ft., From _____ ft. to _____ ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? East and West How many feet? 12.0																																															
<table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th></tr></thead><tbody><tr><td>Surface</td><td></td><td>Stiff Dk. Brown-Black, Med. Plastic Silty Clay w/ rock fragment, wood, cinder</td><td></td><td></td><td></td></tr><tr><td>Surface</td><td>5.0ft.</td><td>Dense light brown firm sandy silt</td><td></td><td></td><td></td></tr><tr><td>5.0ft.</td><td>10.0ft.</td><td>Same</td><td></td><td></td><td></td></tr><tr><td>10.0ft.</td><td>15.0ft.</td><td>Same</td><td>02</td><td></td><td></td></tr><tr><td>15.0ft.</td><td>20.0ft.</td><td>Dense light brown, fine-Med. silty sand</td><td></td><td></td><td></td></tr><tr><td>20.0ft.</td><td>25.0ft.</td><td>Same</td><td>07</td><td></td><td></td></tr></tbody></table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	Surface		Stiff Dk. Brown-Black, Med. Plastic Silty Clay w/ rock fragment, wood, cinder				Surface	5.0ft.	Dense light brown firm sandy silt				5.0ft.	10.0ft.	Same				10.0ft.	15.0ft.	Same	02			15.0ft.	20.0ft.	Dense light brown, fine-Med. silty sand				20.0ft.	25.0ft.	Same	07		
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG																																										
Surface		Stiff Dk. Brown-Black, Med. Plastic Silty Clay w/ rock fragment, wood, cinder																																													
Surface	5.0ft.	Dense light brown firm sandy silt																																													
5.0ft.	10.0ft.	Same																																													
10.0ft.	15.0ft.	Same	02																																												
15.0ft.	20.0ft.	Dense light brown, fine-Med. silty sand																																													
20.0ft.	25.0ft.	Same	07																																												
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/16/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 399 This Water Well Record was completed on (mo/day/yr) 6-4-91 under the business name of WOODMAN - CLYDE CONSULTANTS by (signature) Robert H. Woodman																																															
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.																																															