

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Wyandotte 105		Sec 1/4 NW 1/4 NW 1/4	21	T 11 S	R 25 EW
Distance and direction from nearest town or city street address of well if located within city? 1806 Kansas Avenue, Kansas City, Kansas 66105					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		1806 Kansas Avenue Kansas City, Kansas 66105			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL			
		51.0 ft. ELEVATION: 41.0 ft.			
		Depth(s) Groundwater Encountered 43.8 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 43.8 ft. below land surface measured on mo/day/yr 11/6/95			
		Pump test data: Well water was . ft. after . hours pumping . gpm			
		Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm			
		Bore Hole Diameter 8.25 in. to 51 . ft., and . in. to . ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes . No .; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes . No .			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued . Clamped .			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded .			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Threaded . +			
Blank casing diameter 2 in. to 36 31 ft. Dia . in. to . ft. Dia . in. to . ft.					
Casing height above land surface 30 in. weight SCH 40 lbs./ft. Wall thickness or gauge No. .					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) .		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 6 Wire wrapped 9 Drilled holes		10 Other (specify) .			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 36 to 31 ft. to 51 ft. From . ft. to . ft.					
GRAVEL PACK INTERVALS: From 29 ft. to 51 ft. From . ft. to . ft.					
6 GROUT MATERIAL:		4 Other Concrete			
1 Neat cement 2 Cement grout 3 Bentonite					
Grout Intervals: From 2 ft. to 29 ft. From . ft. to . ft.		From 0 ft. to 2 ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Fill, cr stone, clay, brick, concrete			
8	17	silt, trace clay, sand lenses			
17	51	fine to coarse sand, with silt & seams			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/9/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 11/3/95 under the business name of Terracon Consultants, Inc. by (signature) Ronell Bullitt					