

1 LOCATION OF WATER WELL:

County: Wyandotte

Fraction

SW 1/4 NW 1/4 NW 1/4

Section Number

21

Township Number

T 11

S

Range Number

R 25

Distance and direction from nearest town or city street address of well if located within city?

1806 Kansas Avenue, Kansas City, Kansas 66105

MW 4

2 WATER WELL OWNER:

Colgate Palmolive Company

RR#, St. Address, Box #

1806 Kansas Avenue

Board of Agriculture, Division of Water Resources

City, State, ZIP Code

Kansas City, Kansas 66105

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL

Depth(s) Groundwater Encountered 1 50.0 ft. 2 42.0 ft. 3 38.75 ft.

WELL'S STATIC WATER LEVEL 38.8 ft. below land surface measured on mo/day/yr 1/6/95

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8.25 in. to 50 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

- 1 Steel
2 PVC
3 RMP (SR)
4 ABS

5 Wrought iron

- 6 Asbestos-Cement
7 Fiberglass

8 Concrete tile

- 9 Other (specify below)

CASING JOINTS: Glued Clamped

Welded

Threaded

Blank casing diameter 2 in. to 35 ft. Dia. in. to ft. Dia. in. to ft.

Casing height above land surface -2.75 in. weight SCH 40 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

- 1 Steel
2 Brass
3 Stainless steel
4 Galvanized steel

5 Fiberglass

6 Concrete tile

7 PVC

8 RMP (SR)

9 ABS

10 Asbestos-cement

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

- 1 Continuous slot
2 Louvered shutter
3 Mill slot
4 Key punched

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

8 Saw cut

9 Drilled holes

10 Other (specify)

11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 35.0 ft. to 50.0 ft. From 35.0 ft. to 50.0 ft. From 35.0 ft. to 50.0 ft.

GRAVEL PACK INTERVALS: From 31.0 ft. to 50.0 ft. From 31.0 ft. to 50.0 ft. From 31.0 ft. to 50.0 ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Concrete

Grout Intervals: From 2.0 ft. to 31.0 ft. From 31.0 ft. to 50.0 ft. From 50.0 ft. to 50.0 ft.

What is the nearest source of possible contamination:

- 1 Septic tank
2 Sewer lines
3 Watertight sewer lines
4 Lateral lines
5 Cess pool
6 Seepage pit
7 Pit privy
8 Sewage lagoon
9 Feedyard

10 Livestock pens

11 Fuel storage

12 Fertilizer storage

13 Insecticide storage

14 Abandoned water well

15 Oil well/Gas well

16 Other (specify below)

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	6.0	Fill sand gravel clay brick			
6.0	9.5	5 ft trace clay gray			
9.5	16.5	Fine to medium sand with occ. silt & clay			
16.5	27.0	Sand with silt and clay seams			
27.0	50.0	Fine to coarse sand with clay & gravel layers			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/12/94 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 416

This Water Well Record was completed on (mo/day/yr) 1/31/95

under the business name of Terracon Consultants, Inc.

by (signature) Ronald E. Bullock